


FEATURES

Single Turn/ Cermet/ Industrial/ Sealed
Many Terminal Styles

PICTURE



Electrical Characteristics

Standard Resistance Range	10Ω - 5MΩ
Resistance Tolerance	±10% ; ±20% for 10 ohm
Absolute Minimum Resistance	≤10Ω (100Ω ≤ R ≤ 1KΩ)
Contact Resistance Variation	≤1%R (R > 1KΩ) (whichever is larger)
Contact Resistance	CRV ≤ 3%R or 5Ω
Insulation Resistance	R1 ≥ 1GΩ (100Vac)
Withstand Voltage	220VDC
Effective Travel	300° ± 10°


Environmental Characteristics

Power Rating (315volts max)	0.5W@70°C, 0W@125°C
Temperature Range	-55°C ~ +125°C
Temperature Coefficient	±200ppm/°C (±100ppm/°C on request)
Temperature Variation	-55°C, 30min, +125°C 30min, 5 cycles ΔR ≤ 5%R, Δ(Uab/Uac) ≤ 10%
Collision	100m/s ² , 4000cycles, ΔR ≤ 2%R
Electrical Endurance at 70°C	0.5W@70°C, 1000h ΔR ≤ 10%R Δ(Uab/Uac) ≤ 10%, CRV ≤ 3% or 5Ω (whichever is larger)
Rotational Life	200 cycles ΔTR ≤ 10%R, CRV ≤ 3% or 5Ω (whichever is larger)


Physical Characteristics

Starting Torque	≤ 35mN·m
Marking	Resistance Tolerance (When no identification, it is of ± 10%) Resistance Code, Model
Standard Packaging	50pcs, per tube


Common Dimensions




1028B




1028C



1028H



RKT-3386J




Resistance Table


Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	151
250	201
300	251
470	471
500	501
680	681
1,000	102
1,500	152
2,000	202
2,200	222
2,500	252
3,000	302
4,700	472
5,000	502
6,800	682
10,000	103
15,000	153
20,000	203
22,000	223
25,000	253
30,000	303
33,000	333
47,000	473
50,000	503
68,000	683
100,000	104
150,000	154
200,000	204
220,000	224
250,000	254
300,000	304
330,000	334
470,000	474
500,000	504
680,000	684
1,000,000	105
2,000,000	205
2,200,000	225
5,000,000	505

Special resistances available.

1028K




1028G




1028 (STYLE) -EY5-(RESISTANCE CODE)


Side Adjust




Top Adjust




1028M



1028V




1028P




1028 (STYLE)-EY5-(RESISTANCE CODE)-T

The Model 3386 is available with a knob for finger adjustment. Add suffix letter "T" to order code.



1028R



Note: Specifications are subject to change without notice.