



LED Signalleuchten LED Panel Mount Indicators

Standardreflektor flache Linse mit Vorwiderstand und Einweggleichrichter IP67 / Standard bezel flat lens with resistor and half-wave rectifier IP67



| Part Number | Colour | Voltage | Typ. Current | Typ. Lumi. Intensity |
|--|--------|-----------|-------------------|----------------------|
| Schwarzer Kunststoffreflektor / Black plastic bezel | | | | |
| 19381250 | red | 12V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19381255 | green | 12V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19381252 | yellow | 12V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19381257 | blue | 12V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938125W | white | 12V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| 19381350 | red | 24V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19381355 | green | 24V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19381352 | yellow | 24V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19381357 | blue | 24V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938135W | white | 24V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| Hochglanzverchromter Metallreflektor / Satin chrome bezel | | | | |
| 19380250M | red | 12V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19380255M | green | 12V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19380252M | yellow | 12V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19380257M | blue | 12V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938025WM | white | 12V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| 19380350M | red | 24V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19380355M | green | 24V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19380352M | yellow | 24V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19380357M | blue | 24V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938035WM | white | 24V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| Schwarzverchromter Metallreflektor / Black chrome bezel | | | | |
| 19381250M | red | 12V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19381255M | green | 12V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19381252M | yellow | 12V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19381257M | blue | 12V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938125WM | white | 12V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| 19381350M | red | 24V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19381355M | green | 24V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19381352M | yellow | 24V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19381357M | blue | 24V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938135WM | white | 24V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| Mattverchromter Metallreflektor / Matt chrome bezel | | | | |
| 19382250M | red | 12V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19382255M | green | 12V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19382252M | yellow | 12V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19382257M | blue | 12V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938225WM | white | 12V AC/DC | 2,5mA AC / 5mA DC | 750mcd |
| 19382350M | red | 24V AC/DC | 8mA AC / 16mA DC | 1500mcd |
| 19382355M | green | 24V AC/DC | 7mA AC / 14mA DC | 1200mcd |
| 19382352M | yellow | 24V AC/DC | 8mA AC / 16mA DC | 1000mcd |
| 19382357M | blue | 24V AC/DC | 7mA AC / 14mA DC | 350mcd |
| 1938235WM | white | 24V AC/DC | 2,5mA AC / 5mA DC | 750mcd |

Lichtstärkedaten der verwendeten LED bei DC-Betrieb / Luminous intensity data of the LED on direct voltage

Maximale Frontplattenstärke 11mm / Maximum panel thickness 11mm

Andere Spannungen auf Anfrage / Other voltages on request

EINBAUDURCHMESSER
MOUNTING HOLE

6 mm

8 mm

12 mm

14 mm

16 mm

19 mm

22 mm

ZUBEHÖR
ACCESSORIES