

EPIC® DATA PB TR M12

M12 Terminating resistor for PROFIBUS

Extremely robust M12 bus termination (resistor) for individual use within field bus networks (PROFIBUS, DeviceNet and CANopen).



Automation



Assembly time



Space requirement

Info

Fully suitable for industrial use

Application range

Mechanical and plant engineering

Benefits

Cost efficient termination of a bus systems

Space-saving due to compact dimensions

Robust design

Product Make-up

Straight connector M12 with integrated termination resistor

Straight connector M12, with integrated termination resistor, shielded

Product features

150 Ω terminating resistor for PROFIBUS

Technical Data

Coding:	B - inverse (PROFIBUS)
Contact material:	CuSn
Rated current (A):	4 A
Protection rating:	IP65/IP67 (plug) IP 67 (socket)
Ambient temperature (operation):	-25 °C to +90 °C (plug) -40 °C to +85 °C (socket)

Note

Photographs are not to scale and do not represent detailed images of the respective products.





EPIC® DATA PB TR M12

Part number	Article designation	Number of pins	Rated voltage (V)	PU
Plug, unshielded (terminating resistor)				
22260722	AB-C4-M12MS-PB-TR	4	60	5
Socket, shielded (terminating resistor)				
22261001	AB-C5-M12FS-PB-TR-SH	4	32	1

EPIC® DATA PB TR M12

