

PRODUCT

Integrity 120gsm 100% Polyester Wipes

Constant of the second se

The light weight laser sealed edged Polyester wiper is a double knit 100% continuous-filament polyester. All four edges are laser cut and sealed to prevent particle and fibre release.

FEATURES

- Laser sealed edges ensure ultra low lint and particle level
- Good absorbency and wiping efficiency
- Resists abrasion under rigorous use
- Available in various sizes and packaging configurations
- Solvent safe, double bagged and vacuum cleanroom packed
- Available sterile by gamma irradiation

PLEASE NOTE

Data shown are typical values and should not be used as specifications.

APPLICATIONS

- Suitable for class ISO 4-6 cleanrooms
- Cleaning of surfaces to control submicron particles, fibres, and chemical residue

ORDER CODES	PACK QTY	SIZE
600-0230	200 wipes	7"x7" – Stack
600-0210	150 wipes	12"x12" – Bulk
600-0203	150 wipes	9"x9" – Bulk

To request a quotation or for more information, please call **+44 (0)1473 836205** email **info@integritycleanroom.co.uk** or visit **www.integritycleanroom.co.uk**

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © 2023 Integrity Cleanroom.



TESTING

PERFORMANCE CHARACTERISTICS		
Basis Weight	120 ± 5 gsm	
Thickness (micrometer)	0.42mm - 0.50mm	
Absorbency Rate & Capacity (IEST-RP-CC004.3, Sec 8.1)	≥ 250ml/m²	
Absorbency Rate (IEST-RP-CC004.3, Sec 8.2)	≤ 1.0 sec	

CONTAMINATION CHARACTERISTICS		
Non-volatile Residue, NVR (IEST-RP-CC 004.3, Sec 7.1.2) DI Water IPA	0.050 mg/g 0.067 mg/g	
Organics by FTIR (IEST-RP-CC004.3, Sec 7.2.1) Ionics, IC (IEST-RP-CC004.3, Sec 7.2.2) Chloride (Cl) Sodium (Na) Calcium (Ca) Potassium (K) Magnesium (Mg)	No silicone oil, amide and DOP detected 0.020 ppm 0.0398 ppm 0.037 ppm 0.0262 ppm No Detection	

RELEASABLE PARTICLES		
By LPC (≥ 0.5 um) (IEST-RP-CC 004.3, Sec 6.1.4)	700 counts/cm ²	
By APC sizes ≥ 0.5 um (IES-RP-CC003.2,Helmke Drum Test @10rpm)	50 counts/pc - 9"x9"	

To request a quotation or for more information, please call +44 (0)1473 836205 email info@integritycleanroom.co.uk or visit www.integritycleanroom.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information liced or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © 2023 Integrity Cleanroom.