

METERS**NEW****DUAL USB CHARGER WITH VOLT / AMP METER****P/No. A13-233 SERIES****Features:**

- Rating : Input : 12~24V DC. USB.output : 5V 2.4A + 2.4A max., 2 ports
- **A13-233A-01-BBIR : Voltage / Ampere meter.**
Measuring voltage range: 9~33V DC
Measuring current range: 0~4.8A
0.250" quick terminals
- **A13-233A-11-BBRV : Voltage meter.**
Measuring current range : 9~33V DC
22AWG wire with 0.250" quick terminals
- Reversed polarity protection
- 3-digital LED display, available with red, amber and blue colors
- Display lens colors are available with 1) transparent ink for Red, amber and blue color display, 2) transparent red for red color display, 3) transparent green for amber color display and 4) transparent blue for blue color display
- Snap in USB charger with waterproof cap, rated IP64
- Optional accessories : Sealed pad. Panel #PR18-E2/3/4-B.Connector #R4-63B for terminal type only
- Mounting hole : 36.8 x 21.0mm
- Size: 43.6 (L) x 24.4 (W) x 52.9 (H) mm (Terminal not included.)

IP 64

**DUAL LED DIGITAL DC VOLTMETER****P/No. A25-6B****Features:**

- Rating : Operating voltage : 7~33V DC.
- Dual 3-digital LED displays, available with red, green and blue colors
- Reverse polarity protection
- Surge protection up to 400W/35V
- Terminals : 0.178" quick terminals
- Mounting hole : 29mm dia.
- Size : \varnothing 36.8(D) x 60.0(H) mm

**LED DIGITAL DC VOLT / AMP METER****P/No. A25-7****Features:**

- Rating : Operating voltage : 7~33V DC.
Measuring voltage range : 7~33V DC
Long time use suggestion to 0~70A.
Measuring current range : 0~100A
- 3-digital LED display, available with red, green and blue colors
- Reverse polarity protection
- Surge protection up to 400W/36V
- Shunt : 100A/100mV, with cover
- Suitable for a variety of applications : Marine cockpits, caravans, 4x4s, and RVs
- Optional accessories : single / dual mounting panel & surface mount cases
- Mounting hole : 29mm diameter
- Size : Meter -- \varnothing 36.8(D) x 60.0(H) mm
Shunt – 70(L) x 50(W) x 50(H) mm



*Shunt with cover

***All the specifications are subject to change without notice.**

Headquarters:
TEL : 886-6-2532181
FAX : 886-6-2532633

Taipei Branch Office:
TEL : 886-2-25014062-4
FAX : 886-2-25040685

China Factory:
TEL : 86-752-3897988
FAX : 86-752-3897986
www.shinchin-sci.com

Hong Kong Branch:
TEL : 852-27939773
FAX : 852-27939830

Indonesia Factory:
TEL : 62-24-7627048
FAX : 62-24-7627047