

acar 504 W

Surge protective power strip
+ two fast blow fuses



5 socket outlets with earthing pin
with safety shutters for protection against electric shock

High quality power cord
H05VV-F



Two fuses

Illuminated double pole mains switch

- 5 SOCKET OUTLETS WITH EARTHING PIN
- TWO FUSES
- SOCKET OUTLETS SAFE FOR CHILDREN
- SURGE PROTECTION
- ILLUMINATED DOUBLE POLE MAINS SWITCH
- AVAILABLE POWER CORD LENGTHS: 1.5m, 3m, 5m


The **acar 504 W** is the classical model in the range of surge protective devices offered by HSK DATA, featuring high durability and reliability, appreciated by a huge number of satisfied users due to its long-term operation. The device has five protected socket outlets 230V with earthing and 2 fast blow fuses. Additionally, the included mounting brackets allow permanent installation of the device in any convenient location. The illuminated power switch indicates presence of voltage in protected socket outlets.

Technical data: acar 504 W

Maximum load	P_{MAX} 2300W
Nominal voltage U_N	230V
Nominal frequency	50Hz
Nominal load current	$\Sigma I_N = 10A$ MAX
Surge protection response time	<25ns
Maximum voltage U_C	250V 50Hz
Protection level U_p	$\leq 1.3kV$
Nominal discharge current i_N	2kA (L/N) – 8/20 μs
Maximum discharge current i_{MAX}	6.5kA (L/N) – 8/20 μs
Fuses	two fuses 10A/250V
Anti-shock protection system	earthing pins connected to the protective earthing conductor
Number of socket outlets	5 two-pole socket outlets with earthing pin, 10A/250V
Switch	illuminated double pole mains switch
Housing	made of self-extinguishing plastic
Dimensions	385x59x55/43mm
Weight	0.54kg



ILLUMINATED DOUBLE POLE MAINS SWITCH AND 2 FUSES



5 SOCKET OUTLETS 10A WITH EARTHING PIN AND SAFETY SHUTTERS



MOUNTING BRACKETS INCLUDED

The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress. ATTENTION! The technical data define the maximum values of surges against which the device protects.