



mini
axon[®]

mini axon A210

Surge protective adapter
+ surge protection indicator



Safety shutters

Power plug integrated
with the housing

2 socket outlets
with earthing pin

Surge protection indicator

**2 SOCKET OUTLETS
WITH EARTHING PIN**

**SURGE
PROTECTION**

**SOCKET OUTLETS
SAFE FOR CHILDREN**

**SURGE PROTECTION
INDICATOR**



The **mini axon A210** is a very practical surge protector for two appliances. Surge protection system, ergonomic design and compact size make the **mini axon A210** an effective protection of power supply for electronic controllers used in central heating furnaces. Despite the reduced dimensions, the device features the highest surge protection parameters. Additionally, the **mini axon A210** is equipped with the indicator of proper operation of the surge protection and shutters to protect against electric shock.

Technical data: **mini axon A210**

Maximum load	P _{MAX} 2300W
Nominal voltage U _N	230V
Nominal frequency	50Hz
Nominal load current	ΣI _N = 10A MAX
Surge protection response time	<25ns
Maximum voltage U _C	250V 50Hz
Protection level U _p	≤1.3kV
Nominal discharge current i _N	2kA (L/N) – 8/20μs
Maximum discharge current i _{MAX}	6.5kA (L/N) – 8/20μs (type 2)
Anti-shock protection system	earthing pins connected to the protective earthing conductor
Number of socket outlets	2 two-pole socket outlets with earthing pin, 10A/250V
Housing	made of self-extinguishing plastic
Dimensions	130x56x74mm
Weight	0.12kg

2 SOCKET OUTLETS 10A
WITH EARTHING PIN
AND SAFETY SHUTTERS



SURGE PROTECTION
INDICATOR



The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress.
ATTENTION! The technical data define the maximum values of surges against which the device protects.