SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Printer AG

Creation date	15th June 2022		
Revision date	23rd February 2023	Version	8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier — Printer AG

Substance / mixture — mixture

UFI — 4F00-G0E7-G00J-4C5M

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Cleaning agent.

Main intended use

PC-INK-OTH — Other inks, toners and related printing materials

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Distributor

Name or trade name	Transfer Multisort Elektronik Ltd.
Address	Birmingham Coleshill House Suite 1C, 1 Station Road, Coleshill United Kingdom
Phone	+44 1675790026
E-mail	office@tme-uk.eu

Manufacturer

Name or trade name	AG TermoPasty Grzegorz Gąsowski
Address	Kolejowa 33 E, Sokoły, 18-218 Poland
Identification number (CRN)	200133730
VAT Reg No	PL9661767714
Phone	862741342
E-mail	biuro@termopasty.pl
Web address	www.termopasty.pl

Competent person responsible for the safety data sheet

Name	AG TermoPasty Grzegorz Gąsowski
E-mail	biuro@termopasty.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222
Asp. Tox. 1, H304
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H336
Repr. 2, H361f
STOT RE 2, H373
Aquatic Chronic 2, H411

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram

Signal word

Danger

Hazardous substances

propan-2-ol
n-hexane

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 122 °F.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	27-36	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	2
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX	propan-2-ol	20-40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	2

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	9-18	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
Index: 601-037-00-0 CAS: 110-54-3 EC: 203-777-6 Registration number: 01-2119480412-44-XXXX	n-hexane	4,4-22	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411 Specific concentration limit: STOT RE 2, H373: C ≥ 5 %	2
Index: 601-006-00-1 CAS: 109-66-0 EC: 203-692-4 Registration number: 01-2119459286-30-XXXX	pentane	4,95-6,05	Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH066	1, 2
EC: 931-254-9 Registration number: 01-2119459286-30-XXXX	Hydrocarbons, C6, isoalkanes, <5% n-hexane	4,95-6,05	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	
Index: 601-017-00-1 CAS: 110-82-7 EC: 203-806-2	cyclohexane	<1,1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	2, 3

Notes

1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

2 A substance for which exposure limits are set.

3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

DO NOT INDUCE VOMITING! If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale gases and vapours. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. Do not allow to enter drains.

6.3. Methods and material for containment and cleaning up

Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale gases and vapours. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
400 ml	airspray	FE

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union **Commission Directive 2006/15/EC**

Substance name (component)	Type	Value
n-hexane (CAS: 110-54-3)	OEL 8 hours	72 mg/m³
	OEL 8 hours	20 ppm
pentane (CAS: 109-66-0)	OEL 8 hours	3000 mg/m³
	OEL 8 hours	1000 ppm
cyclohexane (CAS: 110-82-7)	OEL 8 hours	700 mg/m³
	OEL 8 hours	200 ppm

United Kingdom **EH40/2005 Workplace exposure limits (Fourth Edition 2020)**

Substance name (component)	Type	Value
butane (CAS: 106-97-8)	WEL 8h	1450 mg/m³
	WEL 8h	600 ppm
	WEL 15min	1810 mg/m³
	WEL 15min	750 ppm
propan-2-ol (CAS: 67-63-0)	WEL 8h	999 mg/m³
	WEL 8h	400 ppm
	WEL 15min	1250 mg/m³
	WEL 15min	500 ppm
n-hexane (CAS: 110-54-3)	WEL 8h	72 mg/m³
	WEL 8h	20 ppm
pentane (CAS: 109-66-0)	WEL 8h	1800 mg/m³
	WEL 8h	600 ppm
cyclohexane (CAS: 110-82-7)	WEL 8h	350 mg/m³
	WEL 8h	100 ppm
	WEL 15min	1050 mg/m³
	WEL 15min	300 ppm

DNEL

n-hexane

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	93 mg/m³	Chronic effects systemic		
Workers	Dermal	13 mg/kg/24h	Chronic effects systemic		
Consumers	Inhalation	20 mg/m³	Chronic effects systemic		
Consumers	Oral	6 mg/kg/24h	Chronic effects systemic		
Consumers	Dermal	7 mg/kg/24h	Chronic effects systemic		

propan-2-ol

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	888 mg/kg	Chronic effects systemic		
Workers	Inhalation	500 mg/m³	Chronic effects systemic		
Consumers	Dermal	319 mg/kg	Chronic effects systemic		
Consumers	Inhalation	89 mg/m³	Chronic effects systemic		
Consumers	Oral	26 mg/kg	Chronic effects systemic		

PNEC

propan-2-ol

Route of exposure	Value	Value determination	Source
Drinking water	140.9 mg/l		
Marine water	140.9 mg/l		
Freshwater sediment	552 mg/kg		
Sea sediments	552 mg/kg		
Soil (agricultural)	28 mg/kg		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Respirator.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	colourless
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available

Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	gas
Kinematic viscosity	data not available
Solubility in water	data not available
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	data not available
Relative vapour density	data not available
Particle characteristics	data not available
Form	aerosol

9.2. Other information

Evaporation rate: non-applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

cyclohexane

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	12 g/kg		Rat (Rattus norvegicus)	
Dermal	LD_{50}	>18 g/kg		Rabbit	

n-hexane

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	28.7 g/kg		Rat	
Dermal	LD_{50}	3.295 g/kg		Rabbit	

pentane

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	>2000 mg/kg		Rat	

pentane

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LD_{50}	364 mg/m³	4 hours	Rat	

propan-2-ol

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	5840 mg/kg		Rat (Rattus norvegicus)	
Dermal	LD_{50}	13400 mg/kg		Rabbit	
Inhalation	LC_{50}	25000 mg/m³	4 hours	Rat (Rattus norvegicus)	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways. Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time.

pentane

Route of exposure	Result	Exposure time	Species	Sex
	Negative			

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Toxic to aquatic life with long lasting effects.

n-hexane

Parameter	Value	Exposure time	Species	Environment
LC_{50}	3.9 mg/l	48 hours	Invertebrates (Daphnia magna)	
NOEL	30 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	
LC_{50}	>1000 µg/l	48 hours	Fish (Oryzia latipes)	

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
LC_{50}	9640 mg/l	96 hours	Fish (Pimephales promelas)	
LC_{50}	>10000 mg/l	24 hours	Aquatic invertebrates (Daphnia magna)	
LOEC	1000 mg/l	8 days	Algae (Selenastrum capricornutum)	

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Data not available.

12.4. Mobility in soil

Data not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.	
UN number	1950
Classification code	5F
Safety signs	2.1+hazardous for the environment

Air transport - ICAO/IATA

Packaging instructions passenger	203
Cargo packaging instructions	203

Marine transport - IMDG

EmS (emergency plan)	F-D, S-U
MFAG	620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended.

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

cyclohexane

Restriction	Conditions of restriction
57	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g. 2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010. 3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows: "— This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying.".

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 122 °F.

A list of additional standard phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC_{50}	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD_{50}	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations

UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 8.0 replaces the SDS version from 15 June 2022. Changes were made in sections 1, 2, 12, 13, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.