



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## HIGH VOLTAGE NPN SILICON POWER TRANSISTOR

**BUX80**


**TO-3**

**Metal Can Package**

**RoHS compliant**



TO-3



### FEATURES:

The BUX80 is a silicon multi-epitaxial mesa NPN transistor in Jedec TO-3 metal case, particularly intended for converters, inverters, switching regulators and motor control system applications

### APPLICATIONS:

1. Switching Regulators
2. Motor Controls
3. High Frequency and Efficiency Converters.

### ABSOLUTE MAXIMUM RATINGS ( $T_a = 25\text{ }^\circ\text{C}$ )

Symbol	Parameter	Value	Unit
$V_{CES}$	Collector-emitter Voltage ( $V_{BE} = 0$ )	800	V
$V_{CER}$	Collector-emitter Voltage ( $R_{BE} = 50\ \Omega$ )	500	V
$V_{CEO}$	Collector-emitter Voltage ( $I_B = 0$ )	400	V
$V_{EBO}$	Emitter-base Voltage ( $I_C = 0$ )	10	V
$I_C$	Collector Current	10	A
$I_{CM}$	Collector Peak Current	15	A
$I_B$	Base Current	5	A
$P_{tot}$	Total Power Dissipation at $T_{case} = 40\text{ }^\circ\text{C}$	100	W
$T_{stg}$	Storage Temperature	-65 to 150	$^\circ\text{C}$
$T_j$	Max Operating Junction Temperature	150	$^\circ\text{C}$

### THERMAL DATA

$R_{thj-case}$	Thermal Resistance Junction-case	Max	1.1	$^\circ\text{C/W}$
----------------	----------------------------------	-----	-----	--------------------

BUX80

Rev0\_02052020EM



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company




**ELECTRICAL CHARACTERISTICS** ( $T_A=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{CES}$	Collector Cut-off Current ( $V_{BE} = 0$ )	$V_{CE} = 800\text{ V}$			1	mA
		$V_{CE} = 800\text{ V}$ $T_{case} = 125^\circ\text{C}$			3	mA
$I_{EBO}$	Emitter Cut-off Current ( $I_C = 0$ )	$V_{BE} = 10\text{ V}$			10	mA
$V_{CEO(sus)}$	Collector-Emitter Sustaining Voltage ( $I_B = 0$ )	$I_C = 100\text{ mA}$	400			V
$V_{CER(sus)}$	Collector-Emitter Sustaining Voltage ( $R_{BE} = 50\ \Omega$ )	$I_C = 100\text{ mA}$	500			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 5\text{ A}$ $I_B = 1\text{ A}$			1.5	V
		$I_C = 8\text{ A}$ $I_B = 2.5\text{ A}$			3	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = 5\text{ A}$ $I_B = 1\text{ A}$			1.4	V
		$I_C = 8\text{ A}$ $I_B = 2.5\text{ A}$			1.8	V
$h_{FE}$	DC Current Gain	$I_C = 1.2\text{ A}$ $V_{CE} = 5\text{ V}$		30		
$t_{on}$	Turn-on Time	$I_C = 5\text{ A}$ $I_{B1} = 1\text{ A}$ $V_{CC} = 250\text{ V}$			0.5	s
$t_s$	Storage Time	$I_C = 5\text{ A}$ $I_{B1} = 1\text{ A}$ $I_{B2} = -2\text{ A}$ $V_{CC} = 250\text{ V}$			3.5	s
$t_f$	Fall Time	$I_C = 5\text{ A}$ $I_{B1} = 1\text{ A}$ $I_{B2} = -2\text{ A}$ $V_{CC} = -250\text{ V}$			0.5	s


Pulsed: Pulse duration = 300  $\mu$ s, duty cycle = 1.5 %

### Package Details



All dimensions in mm.

DIM	MIN.	MAX.
A	—	39.37
B	—	22.22
C	6.35	8.50
D	0.96	1.09
E	—	1.77
F	29.90	30.40
G	10.69	11.18
H	5.20	5.72
J	16.64	17.15
K	11.15	12.25
L	—	26.67
M	3.84	4.19



**PIN CONFIGURATION**

- 1. BASE
- 2. EMITTER
- 3. COLLECTOR

### Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-3	100 pcs/pkt	1.3 kg/100 pcs	12.5" x 8" x 1.8"	0.1K	17" x 11.5" x 21"	2K	27.5 kgs



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



### Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

### Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

### Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## Customer Notes

### Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

### Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information.

Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

**Continental Device India Pvt. Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

BUX80

Rev0\_02052020EM