


## I2C Isolator 5 Click



PID: MIKROE-5725

**I2C Isolator 5 Click** is a compact add-on board that offers completely isolated bidirectional communication. This board features [ISO1644](#), a hot-swappable bidirectional I2C isolator with enhanced EMC and GPIOs from [Texas Instruments](#). The ISO1644 provides two bidirectional channels, supporting a completely isolated I2C interface that eliminates the need for splitting I2C signals into separate transmit and receive signals for use with standalone optocouplers. It supports data rates from DC up to 1.7MHz and has a hot swap circuitry to prevent data glitches. This Click board™ makes the perfect solution for transferring digital signals between circuits with different power domains at ambient temperatures.

I2C Isolator 5 Click is supported by a [mikroSDK](#) compliant library, which includes functions that simplify software development. This [Click board™](#) comes as a fully tested product, ready to be used on a system equipped with the [mikroBUS™](#) socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.  
 ISO 14001: 2015 certification of environmental management system.  
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

## Specifications

|                  |  |
|------------------|--|
| Type             | I2C,Isolators  |
| Applications     | Can be used for transferring digital signals between circuits with different power domains at ambient temperatures   |
| On-board modules | ISO1644 - a hot-swappable bidirectional I2C isolator with enhanced EMC and GPIOs from Texas Instruments  |
| Key Features     | Robust galvanic isolation of digital signals withstands 5kVRMS, low power consumption, supports four I2C speeds, three additional GPIO lines ideal for isolation and glitch-free operation, excellent reliability, long operational life, and more |
| Interface        | GPIO,I2C   |
| Compatibility    | mikroBUS   |
| Click board size | M (42.9 x 25.4 mm)   |
| Input Voltage    | 3.3V or 5V   |

## Resources

[mikroBUS™](#)

[mikroSDK](#)

[Click board™ Catalog](#)

[Click boards™](#)

## Downloads

[I2C Isolator 5 click example on Libstock](#)

[I2C Isolator 5 click 2D and 3D files](#)

[ISO1644 datasheet](#)

[I2C Isolator 5 click schematic](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.  
 ISO 14001: 2015 certification of environmental management system.  
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).