

**Mechanical characteristics**  
cables

assembly code

**Components**  
centre contact  
outer contact  
crimp ferrule  
insulator

**Environmental**  
RoHS compliant

**Mechanische Eigenschaften**  
Kabel

Montageanleitung

**Bauteile**  
Innenkontakt  
Außenkontakt  
Crimprohr  
Isolierung



**Umgebung**  
RoHS konform

G 1 : 7806 Belden, 9907 Belden, HPF 195,  
KX 15, LMR-195, RG-58C/U, WCX195  
© CNT-195 Andrew

C3805

<b>Materials / Material</b>	<b>Finish / Oberfläche</b>
CuZn39Pb3	CuNi2Au1.27
CuZn39Pb3	© NiP-Au
SF Cu w	Ni5Au0.2
PTFE	

2002/95/EC ©

c	19564	18.01.08	MA	2004	Datum/date	Name/name	Werkstoff/ material	
	b	16172	15.12.04	BJ	gez./drawn	03.03.	MA	
	a	15482	19.04.04	MA	gepr./appr.	11.03.04	BJ	
					Norm/stand.			
				Maßstab/scale	Benennung/title			
				2:1	© R-SMA Straight Jack R-SMA-Kabelbuchse			
				untol. Maße/ dim. without tolerances according to	Unteri./doc.type	Zeichnungsnr./drawing no.	 Maße/dimensions: mm	
					K	J01151R0021		
Änd./rev. Index	Anderungsmittellung/ revision code	Datum/ date	Name/ name	Ersatz für/ replaces				Original: DIN A4