

MINI DIGITAL CLAMP METER

KPS-PA20 MINI



- Mini digital current clamp
- 26 mm maxilla with illumination
- 4000 counts
- AC / DC voltage, AC current, resistance, capacity, frequency, duty cycle and temperature measurements
- Continuity warning and diode test
- Hold readings on screen
- Backlit display, auto scaling, auto power off and low battery indication
- CAT.III 600V according to EN 61010



KPS-PA20 MINI

MINI DIGITAL CLAMP METER

General	
Power Supply	3×1.5V AAA Batteries
Product Size	208mm x 78mm x 35mm
Product Weight	240g
Certificate	CE/ETL/RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	4000
Auto And Manual Ranging	✓
Auto Power Off	✓

KPS-PA20 MINI

MINI DIGITAL CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	400mV/4V/40V/400V	0.1mV/1mV/10mV/100mV	± (0.8% + 2 dígitos)
	600V	1V	± (1.0% + 2 dígitos)
AC Voltage	400mV/4V/40V/400V	0.1mV/1mV/10mV/100mV	± (1.0% + 10 dígitos)
	600V	1V	± (1.2% + 10 dígitos)
AC Current	4A (<0.5A)	1mA	± (3.5% + 20 dígitos)
	4A	1mA	± (3.0% + 20 dígitos)
	40A (<5A)	10mA	± (3.0% + 10 dígitos)
	40A	10mA	± (2.5% + 10 dígitos)
	400A	0.1A	± (2.5% + 10 dígitos)
	600A	1A	± (1.5% + 5 dígitos)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ	0.1Ω/1Ω/10Ω/100Ω/1kΩ	± (1.2% + 2 dígitos)
	40MΩ	10kΩ	± (2.0% + 5 dígitos)
Capacitance	50nF/500nF/5μF/50μF/100μF	10pF/0.1nF/1nF/10nF/0.1μF	± (4.0% + 10 dígitos)
Frequency	50Hz/500Hz/5kHz/50kHz /100kHz	0.01Hz/0.1Hz/1Hz/10Hz/100Hz	± (1.0% + 5 dígitos)
Duty Cycle	0.1% ~ 99.9%	0.1%	± (2.0% + 5 dígitos)
Temperature	-20°C ÷ 750°C	1°C	± (2.0% + 2 dígitos)

Product Code Information

SKU	KPSPA20MINICBINT
EAN code	8435394710150
UPC code	810053670163
Pcs/export carton	20