UQS-COB-8W-WW-12V     Professional Led Strip, 8W/m		
		■ Features:
		Uniform lighting
+D024V CL = 405024V	+0547	• Uniform light line and high luminous intensity
ONG CTO SNB	GND CALD GAD	• 3 years warranty
TECHNICAL DETAILS		UK CE 3 IP33 CRI>90 Image: Second secon
MODEL	UQS-COB-8W-WW-12V	EPREL
Supply voltage	12V ± 0.5Vdc	
Power	8W/m (40W/reel)	C ENERG <sup>1</sup>
Current	0.66 A/m (3.3A/roll)	MW LIGHTING
Power per reel	40W	UQS-COB-8W-WW-12V
Color temperature	3000K	A
Beam angle	180°	в
Luminous flux	700 lm/m (3500lm/roll)	C
CRI	>90	
Maximum length for one sided supply	5m	E
IP protection degree	IP20	
Working temperature	-20°C ÷ 50°C	
Storage temperature	-30°C ÷ 80°C	G
LED QTY	320 LEDs/m (1600 LEDs/reel)	4
Width PCB	8mm	kWh/1000h
Cut section	25mm	
Connection wire	2 x AWG20 (0.52 mm2 ) stranded wir length = 360 mm: V+: red: V-:black.	2019/2015
Dimensions (L x W x H)	5004 x 8 x 2.2 mm	
Packing	5m / reel (bag)	

## MECHANICAL SPECIFICATION:

