



# UQS-COB-8W-WW-24V

Professional Led Strip, 8W/m



## ■ Features:

- Uniform lighting
- Uniform light line and high luminous intensity
- 3 years warranty




## TECHNICAL DETAILS

MODEL	UQS-COB-8W-WW-24V	EPREL
Supply voltage	24V ± 0.5Vdc	
Power	8W/m (40W/reel)	
Current	0.33 A/m (1.65A/roll)	
Power per reel	40W	
Color temperature	3000K	
Beam angle	180°	
Luminous flux	740 lm/m (3700lm/roll)	
CRI	>90	
Maximum length for one sided supply	5m	
IP protection degree	IP20	
Working temperature	-20°C ÷ 50°C	
Storage temperature	-30°C ÷ 80°C	
LED QTY	320 LEDs/m (1600 LEDs/reel)	
Width PCB	8mm	
Cut section	50m	
Connection wire	2 x AWG20 (0.52 mm <sup>2</sup> ) stranded wire, length = 360 mm: V+: red: V-:black.	
Dimensions (L x W x H)	5004 x 8 x 2.2 mm	
Packing	5m / reel (bag)	



MW LIGHTING  
UQS-COB-8W-WW-24V



4  
kWh/1000h



2019/2015

## MECHANICAL SPECIFICATION:

