

## tesa® 51036

### PET cloth tape for high abrasion protection

tesa® 51036 is a PET cloth wire harness tape with an advanced acrylic adhesive (triple A®).

#### Major Features:

- High temperature resistance 150°C/3000h
- High abrasion resistance

Colour: Black and orange

### Main Application

tesa® 51036 is designed for the engine compartment, providing high abrasion protection.

### Technical Data

|                               |                  |                                      |                         |
|-------------------------------|------------------|--------------------------------------|-------------------------|
| ▪ Backing material            | PET cloth        | ▪ Temperature resistance (3000h)     | 150 °C                  |
| ▪ Total thickness             | 260 µm           | ▪ Abrasion resistance (10mm mandrel) | Class D (acc. to LV312) |
| ▪ Type of adhesive            | advanced acrylic | ▪ Abrasion resistance (5mm mandrel)  | Class D (acc. to LV312) |
| ▪ Adhesion to steel           | 5 N/cm           | ▪ Flame resistance as composite      | Class B (acc. to LV312) |
| ▪ Elongation at break         | 40 %             | ▪ Unwind force (roll width > 9mm)    | 11 N/roll (30 m/min)    |
| ▪ Tensile strength            | 275 N/cm         | ▪ Noise damping (decibel)            | Class A (acc. to LV312) |
| ▪ Temperature resistance min. | -40 °C           |                                      |                         |

For latest information on this product please visit <http://l.tesa.com/?ip=51036>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.