



Product: [8471ELV](#)

Electronic, 2 C #16 Str TC, PE Ins, LSZH Jkt, B2ca

[Request Sample](#)

Product Description

Electronic, 2 Conductor 16AWG (19x29) Tinned Copper, PE Insulation, LSZH Outer Jacket, CPR B2ca

Technical Specifications

Product Overview

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
PE - Polyethylene	2.67 mm	0.05 mm	0.018 in

Color Chart

Number	Color
Pair 1	Black & White

Inner Shield

Material
No Shield

Outer Shield

Material
No Shield

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	7.1 mm	0.89 mm

Construction and Dimensions

Stranding

Twists
6 twist/ft

Cabling

Description
1 pair covered with a polyester foil

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

14.7 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor

52 pF/m

Inductance

Nominal Inductance

0.17 μ H/ft

Nominal Pair Inductance

0.62 μ H/m

Current

Element

Max. Recommended Current [A]

Conductor(s) 7.1 Amps per Conductor

Voltage

Voltage Rating [V]

300 V

Temperature Range

Installation Temperature Range: -15°C To +80°C

Storage Temperature Range: -45°C To +80°C

Operating Temp Range (Flexible Install): -15°C To +80°C

Operating Temp Range (Fixed Install): -45°C To +80°C

Mechanical Characteristics

Oil Resistance: IEC 60811-404

Max. Pull Tension: 127 N

Min. Bend Radius During Installation: 71 mm

Min. Bend Radius/Minor Axis: 2.5 in

Standards

CPR Euroclass: B2ca-s1,d1,a1

CENELEC Compliance: EN 50290-2-27

Applicable Environmental and Other Programs

Environmental Space: Indoor - Euroclass B2ca

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

Suitability

Suitability - Indoor: Yes

Suitability - Non-Halogenated: Yes

Suitability - Sunlight Resistance: Yes

Flammability, LSOH, Toxicity Testing

IEC Flammability: IEC 60332-1-2

IEC 60754-1 - Halogen Amount: Zero

IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity: 2.5 μ S/mm

IEC 60754-2 - Halogen Acid Gas Amount - Min. pH: 4.3

IEC 61034-2 - Smoke Density Min. Transmittance: 60%

Plenum/Non-Plenum

Plenum (Y/N): No

History

Update and Revision: Revision Number: 0.21 Revision Date: 04-08-2022

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.