



Product Description

Electronic, 2 Conductor 16AWG (19x29) Tinned Copper, LSZH Insulation, LSZH Outer Jacket

Technical Specifications

Product Overview

Product Overview	
Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; computer communication; panel wiring
Construction Details	
Conductor	
Size Stranding Mate	
16 19x29 TC - Tinne	d Copper
Insulation	
Materia	al Nom. Insulation Diameter Color Code Notes
LSZH - Low Smoke Zero Halo	ogen (Flame Retardant) 2.67 mm (0.105 in) Black & White Flame Retardant
Outer Jacket	
Materia	al Nom. Thickness Nom. Diameter
LSZH - Low Smoke Zero Halo	ogen (Flame Retardant) 0.89 mm (0.035 in) 7.1 mm (0.28 in)
Overall Cable Diameter	7.1 mm (0.28 in)
(Nominal):	
Electrical Characteris	itics
Electricals	
Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond Max. Current
14.7 Ohm/km (4.48 Ohm/100	
Mechanical Character	ristics
Temperature	
Operating Installation	on Storage
-20°C To +75°C -15°C To +8	
Den d De dius	
Bend Radius	
71 mm (2.8 in)	
Max Bull Tension:	127 N (28 6 Inft

Max. Pull Tension: 127 N (28.6 lbf)					
Bulk Cable Weight: 32 lbs/1000ft					
Standards and Compliance					

Environmental Suitability: Indoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight Resistance					
Flammability / Reaction to Fire: IEC 60332-1-2, IEC 60332-3-24					
CPR Compliance:	CPR Euroclass: Dca-s1,d1,a1; CPR UKCA Class: Dca-s1,d1,a1				

CENELEC Compliance: EN 50290-2-20 European Halogen Free Standards: IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3 European Directive Compliance: EU CE Mark	ISO/IEC Compliance:	IEC 61034-2 - Smoke Density Min Transmittance = 60%
Standards: - Halogen Acid Gas Amount - Min. pH = 4.3 European Directive FLI CE Mark	CENELEC Compliance:	EN 50290-2-20
		IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
		EU CE Mark
UK Regulation Compliance: UKCA Mark	UK Regulation Compliance:	UKCA Mark

History

Update and Revision:

Revision Number: 0.325 Revision Date: 12-22-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
8471NH.01500	Blue	Reel	500 m	8719605018359
8471NH.00152	Chrome	Reel	152 m	8719605018328
8471NH.00305	Chrome	Reel	305 m	8719605018335
8471NH.00500	Chrome	Reel	500 m	8719605018342
8471NH.001000	Chrome	Reel	1,000 m	8719605018304
8471NH.001500	Chrome	Reel	1,500 m	8719605018311
8471NH.021000	Green	Reel	1,000 m	8719605148087
8471NH.03305	White	Reel	305 m	8719605197290
8471NH.03500	White	Reel	500 m	8719605161666
8471NH.031000	White	Reel	1,000 m	8719605161680

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.