


Part Number: 8471NH





Product Description

AWG16 (19xAWG29) tinned copper

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass B2ca
Suitable Applications:	Instrumentation and computer cable; For data transmission applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1
Conductor Count:			
Total N	Number of Pa	airs:	
Conductor Size:			

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
FRPE - Flame Retardant Polyethylene	2.67 mm	0.05 mm	0.018 in

Color Chart

Number	Color
Pair 1	Black & White

Inner Shield Material



Inner Jacket Material



Outer Shield Material



Outer Jacket Material

Material	Color	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	Chrome (like RAL 7037)	7.1 mm	0.89 mm

Construction and Dimensions

Stranding



Cabling



Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 14.7 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor 52 pF/m

Inductance

Nominal Inductance	Nominal Pair Inductance
0.17 µH/ft	0.62 μH/m

Current

Element	Max. Recommended Current [A]
Conductor	7.1 A

Voltage

UL Voltage Rating	Voltage Rating [V]
300 V RMS	300 V

Temperature Range

Installation Temp Range:	-15°C To +80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range:	-20°C To +75°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-404
Bulk Cable Weight:	32 lbs/1000ft
Max Recommended Pulling Tension:	127 N
Min Bend Radius During Installation:	71 mm
Min Bend Radius/Minor Axis:	2.5 in

Standards

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
CPR Euroclass:	B2ca-s1,d1,a1
CENELEC Compliance:	EN 50290-2-27
Other Specification:	BS 7655 section 6.1 table 1, LTS 3

Applicable Environmental and Other Programs

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01

Suitability

	Suitability - Indoor:	Yes
ı	Suitability - Non-Halogenated:	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading
ISO/IEC Flammability:	IEC 60332-3-24

Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero	
UL voltage rating:	300 V RMS	

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

Item #	Color
8471NH.01500	Blue
8471NH.001000	Chrome
8471NH.001500	Chrome
8471NH.00152	Chrome
8471NH.00305	Chrome
8471NH.00500	Chrome

History

Revision Number:	5	

© 2019 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.