

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 25/05/2023 Revision date: 05/05/2023 Supersedes version of: 29/03/2022 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SURFACE 95

UFI : EF4X-68CF-000W-Y6P9

Product code : BDS000517AE
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Cleaners - Precision

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele

Belgium

T +32(0)52/45.60.11 - F +32(0)52/45.00.34 hse@crcind.com - www.crcind.com Supplier: Transfer Multisort Elektronik Ltd.

Coleshill, Birmingham Coleshill House Suite 1C, 1 Station Road

+44 1675790026 e-mail: office@tme-uk.eu

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS09

Signal word (CLP)

: Danger

Contains : propan-2-ol; isopropyl alcohol; isopropanol; 1-methoxy-2-propanol; monopropylene glycol

methyl ether; Hydrocarbons, C6, isoalkanes, <5% n-hexane; pentane

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Other information

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651- 34	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
pentane substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 109-66-0 EC-No.: 203-692-4 EC Index-No.: 601-006-00-1	25 – 50	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 926-141-6 REACH-no: 01-2119456620- 43	10 – 25	Asp. Tox. 1, H304 EUH066
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
Carbon dioxide (CO2) (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	1 – 5	Press. Gas (Comp.), H280

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn,

even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial

hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
Belgium - Occupational Exposure Limits		
Local name	Alcool isopropylique # Isopropylalcohol	
OEL TWA	500 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1000 mg/m³	
OEL STEL [ppm]	400 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	1-Methoxypropanol-2	
IOEL TWA	375 mg/m³	
IOEL TWA [ppm]	100 ppm	
IOEL STEL	568 mg/m³	
IOEL STEL [ppm]	150 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol	
OEL TWA	184 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	369 mg/m³	
OEL STEL [ppm]	100 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
pentane (109-66-0)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Pentane	
IOEL TWA	3000 mg/m³	
IOEL TWA [ppm]	1000 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pentane (109-66-0)	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Pentane, tous isomères # Pentaan, alle isomeren
OEL TWA	1800 mg/m³
OEL TWA [ppm]	600 ppm
OEL STEL	2250 mg/m³
OEL STEL [ppm]	750 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Carbon dioxide (CO2) (124-38-9)	
EU - Indicative Occupational Exposure Li	imit (IOEL)
Local name	Carbon dioxide
IOEL TWA	9000 mg/m³
IOEL TWA [ppm]	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Carbone (dioxyde de) # Koolstofdioxide
OEL TWA	9131 mg/m³
OEL TWA [ppm]	5000 ppm
OEL STEL	54784 mg/m³
OEL STEL [ppm]	30000 ppm
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	500 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	26 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	89 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol ((67-63-0)
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
PNEC (Soil)	
PNEC soil	28 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	160 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	2251 mg/l
1-methoxy-2-propanol; monopropylene glyco	ol methyl ether (107-98-2)
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	553,5 mg/m³
Acute - local effects, inhalation	553,5 mg/m³
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	369 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	43,9 mg/m³
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC aqua (intermittent, freshwater)	100 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	52,3 mg/kg dwt
PNEC sediment (marine water)	5,2 mg/kg dwt
PNEC (Soil)	
PNEC soil	4,59 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
Hydrocarbons, C6, isoalkanes, <5% n-hexand	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	13964 mg/kg bodyweight/day

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane Long-term - systemic effects, inhalation 5306 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 1301 mg/kg bodyweight/day Long-term - systemic effects, inhalation 1131 mg/m³ Long-term - systemic effects, dermal 1377 mg/kg bodyweight/day pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 432 mg/kg bodyweight/day Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day Long-term - systemic effects, inhalation 643 mg/m³			
DNEL/DMEL (General population) Long-term - systemic effects, oral 1301 mg/kg bodyweight/day Long-term - systemic effects, inhalation 1131 mg/m³ Long-term - systemic effects, dermal 1377 mg/kg bodyweight/day pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 432 mg/kg bodyweight/day Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day			
Long-term - systemic effects, oral Long-term - systemic effects, inhalation Long-term - systemic effects, dermal Long-term - systemic effects, dermal 1377 mg/kg bodyweight/day pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day			
Long-term - systemic effects, inhalation Long-term - systemic effects, dermal 1377 mg/kg bodyweight/day pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 432 mg/kg bodyweight/day Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day			
Long-term - systemic effects, dermal pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day			
pentane (109-66-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 432 mg/kg bodyweight/day Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects,oral 214 mg/kg bodyweight/day			
DNEL/DMEL (Workers) Long-term - systemic effects, dermal 432 mg/kg bodyweight/day Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day			
Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 214 mg/kg bodyweight/day	pentane (109-66-0)		
Long-term - systemic effects, inhalation 3000 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects,oral 214 mg/kg bodyweight/day	DNEL/DMEL (Workers)		
DNEL/DMEL (General population) Long-term - systemic effects,oral 214 mg/kg bodyweight/day			
Long-term - systemic effects,oral 214 mg/kg bodyweight/day			
	DNEL/DMEL (General population)		
Long-term - systemic effects, inhalation 643 mg/m³			
Long-term - systemic effects, dermal 214 mg/kg bodyweight/day			
PNEC (Water)			
PNEC aqua (freshwater) 230 μg/l			
PNEC aqua (marine water) 230 μg/l			
PNEC aqua (intermittent, freshwater) 880 µg/l			
PNEC (Sediment)			
PNEC sediment (freshwater) 1,2 mg/kg dwt			
PNEC sediment (marine water) 1,2 mg/kg dwt			
PNEC (Soil)			
PNEC soil 0,55 mg/kg dwt			
PNEC (STP)			
PNEC sewage treatment plant 3600 µg/l			

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless.

Appearance : CO2 propelled liquid.
Odour : characteristic.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : Not available Lower explosion limit : Not available Upper explosion limit : Not available Flash point : -35 °C (closed cup) Auto-ignition temperature : > 200 °C Decomposition temperature : Not available : Not applicable Viscosity, kinematic : < 10 mm²/s at 40 °C Solubility : insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure Vapour pressure at 50°C : Not available : 0,73 g/cm3 at 20 °C Density

Relative density : 0,73 at 20 °C
Relative vapour density at 20 °C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

9.2.2. Other safety characteristics

VOC content : 720 g/l

Additional information : For aerosols data for the product without propellant.

05/05/2023 (Revision date) BE - en 9/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

: Not classified (Based on available data, the classification criteria are not met) Acute toxicity (oral) Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional (initial action)	. Not slabshed (Based on available data, the slabshed to not met)	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
LD50 oral rat	5840 mg/kg bodyweight	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
LD50 oral rat	4016 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	> 25,8 mg/l	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
LD50 oral	> 5000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat (Dust/Mist)	> 4950 mg/l	
pentane (109-66-0)		
LD50 oral rat	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat	> 25,3 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable	
Serious eve damage/irritation	: Causes serious eve irritation.	

Serious eye damage/irritation

pH: Not applicable

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met) Germ cell mutagenicity Not classified (Based on available data, the classification criteria are not met) Carcinogenicity : Not classified (Based on available data, the classification criteria are not met) : Not classified (Based on available data, the classification criteria are not met) Reproductive toxicity

STOT-single exposure : May cause drowsiness or dizziness.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

· ·		
STOT-single exposure	May cause drowsiness or dizziness.	
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.	
Hydrocarbons, C6, isoalkanes, <5% n-h	exane	
STOT-single exposure	May cause drowsiness or dizziness.	
pentane (109-66-0)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)	
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight	
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight	
pentane (109-66-0)		
NOAEC (inhalation, rat, vapour, 90 days)	30 mg/l air	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
SURFACE 95		
Vaporizer	Aerosol	
Viscosity, kinematic	< 10 mm²/s at 40 °C	
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)	
Viscosity, kinematic	1,848 mm²/s	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Viscosity, kinematic	2,4 mm²/s at 20 °C	
Hydrocarbons, C6, isoalkanes, <5% n-h	exane	
Viscosity, kinematic	0,46 mm²/s	
pentane (109-66-0)		
Viscosity, kinematic	0,356 mm²/s	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

05/05/2023 (Revision date) BE - en 11/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
LC50 - Fish [1]	10000 mg/l	
LC50 - Fish [2]	9640 mg/l	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
LC50 - Fish [1]	6812 mg/l	
LC50 - Fish [2]	20800 mg/l	
EC50 - Crustacea [1]	21100 – 25900 mg/l	
EC50 - Other aquatic organisms [1]	2954 mg/l	
ErC50 algae	> 1000 mg/l	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
LC50 - Fish [1]	> 1000 mg/l	
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea	
EC50 - Other aquatic organisms [2]	> 1000 mg/l	
pentane (109-66-0)		
LC50 - Fish [1]	4,26 mg/l	
ErC50 algae	10,7 mg/l	

12.2. Persistence and degradability

SURFACE 95	
Persistence and degradability	Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
Bioconcentration factor (BCF REACH)	< 100	
Partition coefficient n-octanol/water (Log Pow)	0,37	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Partition coefficient n-octanol/water (Log Pow)	> 3	
pentane (109-66-0)		
Partition coefficient n-octanol/water (Log Pow) 3,45		
Carbon dioxide (CO2) (124-38-9)		
Partition coefficient n-octanol/water (Log Pow)	0,83	

12.4. Mobility in soil

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

SURFACE 95

Results of PBT assessment Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information

: No other effects known

Global warming potential (GWP)

: 1 (Fluorinated greenhouse gases - (EC) No 517/2014)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods European List of Waste (LoW) code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	ription			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard o	class(es)			
2.1	2.1	2.1	2.1	2.1
¥22	22	**************************************	2 22	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
o supplementary informati	on available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN)

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

: 1

Limited quantities (RID) : 1L

05/05/2023 (Revision date) BE - en 14/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 720 g/l

Detergent Regulation (648/2004)

Allergenic fragrances > 0.01 %:

d-LIMONENE CITRAL

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%
perfumes	
D-LIMONENE	
CITRAL	

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.