



**Product:** <u>8771</u> ☑

Electronic, 3 C #22 Str TC, PE Ins, OS, PVC Jkt, CM

Request Sample

# **Product Description**

Electronic, 3 Conductor 22AWG (7x30) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

# **Technical Specifications**

### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

### **Construction Details**

#### Conductor

| Element      | No. of Elements | Size   | Stranding | Material           |  |
|--------------|-----------------|--------|-----------|--------------------|--|
| Conductor(s) | 3               | 22 AWG | 7x30      | TC - Tinned Copper |  |

#### Insulation

|   | Element Material |                   | Nom. Thickness     | Nom. Insulation Diameter | Color Code        |  |
|---|------------------|-------------------|--------------------|--------------------------|-------------------|--|
| I | Conductor(s)     | PE - Polyethylene | 0.017 in (0.43 mm) | 0.062 in (1.6 mm)        | Black, Red, Clear |  |

## Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |  |
|-------------|-------------------------|----------|------------------|--|
| Таре        | Bi-Laminate (Alum+Poly) | 100%     | 22 AWG (7x30) TC |  |

### **Outer Jacket**

|   | Material   | Nom. Thickness     | Nom. Diameter      |
|---|--|--------------------|--------------------|
|   | PVC - Polyvinyl Chloride                             | 0.033 in (0.84 mm) | 0.199 in (5.05 mm) |
| Ì | Overall Cable Diameter (Nominal): 0.199 in (5.05 mm) |                    |                    |

# **Electrical Characteristics**

## Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                 |
|--------------|--------------------|-------------------------------|---|------------------------------|
| Conductor(s) | 17.8 Ohm/1000ft    | 23 pF/ft (75 pF/m)            | 41 pF/ft (130 pF/m)                             | 6 Amps per Conductor at 30°C |

## Voltage

UL Voltage Rating 300 V (CM), 300 V (UL AWM 2093)

## **Mechanical Characteristics**

#### Temperature

| UL Temperature | Operating      |  |  |
|----------------|----------------|--|--|
| 60°C           | -20°C to +60°C |  |  |

### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 0.56 in (14 mm) | 2.0 in (51 mm)    |

Max. Pull Tension: 36.4 lbs (16.5 kg)

| Bulk Cable Weight: |
|--------------------|
|--------------------|

#### **Standards and Compliance**

| Environmental Suitability:       | Indoor  |
|----------------------------------|---|
| Sustainability:                  | CA Prop 65  |
| Flammability / Reaction to Fire: | UL 1685 UL loading , IEC 60332-1-2  |
| CPR Compliance:                  | CPR Euroclass: Eca; CPR UKCA Class: Eca   |
| NEC / UL Compliance:             | Article 800, CM   |
| AWM Compliance:                  | AWM 2093  |
| CEC / C(UL) Compliance:          | CM  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark   |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)   |

#### **History**

| Update and Revision: | Revision Number: 0.534 Revision Date: 04-19-2023 |
|----------------------|--|
|                      |  |

# **Part Numbers**

#### Variants

| Item #        | Color  | Putup Type | Length    | UPC/EAN       | Footnote |
|---------------|--------|------------|-----------|---------------|----------|
| 8771.00U152   | Chrome | UnReel     | 152 m     | 8719605019264 |          |
| 8771.01152    | Chrome | Reel       | 152 m     | 8719605019288 |          |
| 8771 060250   | Chrome | Reel       | 250 ft    | 612825215738  |          |
| 8771.00U305   | Chrome | UnReel     | 305 m     | 8719605019271 |          |
| 8771.01305    | Chrome | Reel       | 305 m     | 8719605019295 |          |
| 8771 060500   | Chrome | Reel       | 500 ft    | 612825215745  |          |
| 8771 060U500  | Chrome | UnReel     | 500 ft    | 612825215707  |          |
| 8771 0601000  | Chrome | Reel       | 1,000 ft  | 612825215714  | С        |
| 8771 060U1000 | Chrome | UnReel     | 1,000 ft  | 612825215691  |          |
| 8771.013050   | Chrome | Reel       | 3,050 m   | 8719605019301 |          |
| 8771 06010000 | Chrome | Reel       | 10,000 ft | 612825215721  | CY       |

## © 2024 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.