

Notes:
 1.Material:PA66 UL94 V2;
 2.RoHS Compliant;

| Part No. | Part Name | A | B | C | L | M |
|----------------------|-------------------------|------|------|-----|------|----|
| 41075/42207 | 8G509V41075/8G509V42207 | 8.0 | 6.0 | 7.0 | 45.0 | M4 |
| 42920/43155 | 8G509V42920/8G509V43155 | 3.0 | 8.0 | 8.0 | 5.0 | |
| 40765/41310 | 8G509V40765/8G509V41310 | 5.5 | | | 7.0 | |
| 42138/41319 | 8G509V42138/8G509V41319 | 6.0 | | | 8.0 | |
| 40766/41311 | 8G509V40766/8G509V41311 | 8.0 | | | 10.0 | |
| 42156/42208 | 8G509V42156/8G509V42208 | | | | 12.0 | |
| 43214/43217 | 8G509V43214/8G509V43217 | | | | 13.0 | |
| 42139/41312 | 8G509V42139/8G509V41312 | | | | 15.0 | |
| 42921/43156 | 8G509V42921/8G509V43156 | 10.0 | | | 18.0 | |
| 41299/41322 | 8G509V41299/8G509V41322 | | | | 20.0 | |
| 41300/41324 | 8G509V41300/8G509V41324 | | | | 25.0 | |
| 40695/41321 | 8G509V40695/8G509V41321 | | 30.0 | | | |
| 42168/42209 | 8G509V42168/8G509V42209 | | 32.0 | | | |
| 40602/40685 | 8G509V40602/8G509V40685 | | 34.0 | | | |
| 41301/41325 | 8G509V41301/8G509V41325 | | 35.0 | | | |
| 40786/42210 | 8G509V40786/8G509V42210 | | 36.0 | | | |
| 40768/41313 | 8G509V40768/8G509V41313 | 40.0 | | | | |
| 40769/41314 | 8G509V40769/8G509V41314 | 42.0 | | | | |
| 43200/43201 | 8G509V43200/8G509V43201 | 45.0 | | | | |
| 40782/42211 | 8G509V40782/8G509V42211 | 55.0 | | | | |
| Color: Black/Natural | | | | | | |

DREMEC Befestigungselemente GmbH

DATE

2020.05.20

DIMENSION

TOLERANCE

TITLE

HEX SPACER

SCALE

FIT

$L \leq 4$

± 0.10

PART NAME

8G509V41075

MOLD NO.

/

DRAW

ZHR

UNIT

MM

$4 < L \leq 15$

± 0.20

PART NO.

SEE TABLE

MATERIAL

SEE NOTES

DESIGN

ZHR

VERSION

A0

$15 < L \leq 50$

± 0.30

DWG NO.

E4065


COLOR

SEE TABLE

APPROVAL

FDL

VIEW



$50 < L \leq 100$

± 0.40