



Notes:

1. Color: Black;
2. Male(M3) Torques: $\cong 0.13 \text{ N}\cdot\text{m}$;
3. Male(M4) Torques: $\cong 0.3 \text{ N}\cdot\text{m}$;
3. Male(M5) Torques: $\cong 0.58 \text{ N}\cdot\text{m}$;
4. RoHS Compliant.

Part No.	Article No.	Material	M Thread	A	B	C
42436	8G509V42436	PA66 UL94 HB	M3	5.0	6.0	6.0
42359	8G509V42359			6.0		
42552	8G509V42552	5.0				
42553	8G509V42553	6.0				
41295	8G509V41295	25.0				
42924	8G509V42924	35.0				
42925	8G509V42925	PA66 UL94 V2	M4	12.0	10.0	10.0
42926	8G509V42926			25.0		
42927	8G509V42927			40.0		
43582	8G509V43582		M5	80.0		

DREMEC Befestigungselemente GmbH

DATE

2021-1-7

DIMENSION

TOLERANCE

TITLE

HEX SPACER

SCALE

FIT

$L \leq 4$

± 0.10

ARTICLE NO.

8G509V42436

MOLD NO.

S0417

DRAW

JF

UNIT

MM

$4 < L \leq 15$

± 0.20

PART NO.

SEE TABLE

MATERIAL

SEE TABLE

DESIGN

JF

VERSION

A0

$15 < L \leq 50$

± 0.30

DWG NO.

E4078

COLOR

SEE NOTES

APPROVAL

FDL

VIEW



$50 < L \leq 100$

± 0.40