

Notes:

- 1.RoHS Compliant;
- 2.Top Hole: $\text{Ø}3.18\pm0.05\text{mm}$,
Panel Thickness: 1.57mm;
- 3.Bottom Hole: $\text{Ø}4.75\pm0.08\text{mm}$,
Panel Thickness: 1.5-1.6mm.

Part No.	Part Name	Part No.	Part Name	A
41218	8G820V41218	41785	8G820V41785	6.4
41219	8G820V41219	41786	8G820V41786	7.9
41220	8G820V41220	41787	8G820V41787	9.5
41221	8G820V41221	41788	8G820V41788	11.1
41222	8G820V41222	41789	8G820V41789	12.7
41223	8G820V41223	41790	8G820V41790	14.3
41224	8G820V41224	41791	8G820V41791	15.9
Material: PA66 UL94 V2 Color: Natural		Material: PA66 UL94 V0 Color: Natural		

DREMEC Befestigungselemente GmbH

DATE

2020.03.21

DIMENSION

TOLERANCE

TITLE CUPPED REVERSE LOCKING CIRCUIT BOARD SUPPORT

SCALE

FIT

$L \leq 4$

± 0.10

PART NAME 8G820V41218

MOLD NO. S0375

DRAW PLK

UNIT

MM

$4 < L \leq 15$

± 0.20

PART NO. SEE TABLE

MATERIAL SEE TABLE

DESIGN PLK

VERSION

A0

$15 < L \leq 50$

± 0.30


DWG NO. E4129

COLOR SEE TABLE

APPROVAL

FDL

VIEW



$50 < L \leq 100$

± 0.40