

Notes:

1. RoHS Compliant;
2. Top Hole: $\text{Ø}4.0 \pm 0.08\text{mm}$,
Panel Thickness: 1.57mm;
3. Bottom Hole: $\text{Ø}5.4 \pm 0.08\text{mm}$,
Panel Thickness: 1.5-1.65mm.

| Part No. | Part Name | Material | Color | A |
|----------|-------------|--------------|---------|------|
| 40983 | 8G820V40983 | PA66 UL94 V2 | Black | 6.4 |
| 40984 | 8G820V40984 | | Natural | |
| 42386 | 8G820V42386 | | Black | 9.5 |
| 40985 | 8G820V40985 | | Natural | |
| 40986 | 8G820V40986 | | | 12.7 |
| 40987 | 8G820V40987 | | | 15.9 |
| 41557 | 8G820V41557 | PA66 UL94 V0 | Natural | 6.4 |
| 41558 | 8G820V41558 | | | 9.5 |
| 41559 | 8G820V41559 | | | 12.7 |
| 41560 | 8G820V41560 | | | 15.9 |

DREMEC Befestigungselemente GmbH

DATE

2020.03.21

DIMENSION

TOLERANCE

TITLE CUPPED REVERSE LOCKING CIRCUIT BOARD SUPPORT

SCALE

FIT

$L \leq 4$

± 0.10

PART NAME 8G820V40983

MOLD NO. S0467

DRAW PLK

UNIT

MM

$4 < L \leq 15$

± 0.20

PART NO. SEE TABLE

MATERIAL SEE TABLE

DESIGN PLK

VERSION

A0

$15 < L \leq 50$

± 0.30


DWG NO. E4088

COLOR SEE TABLE

APPROVAL

FDL

VIEW



$50 < L \leq 100$

± 0.40