



This position doesn't exist once "A"=4.8

Notes:

- 1. Color: Natural;
- 2. RoHS Compliant;
- 3. Top Hole: $\text{Ø}4.0 \pm 0.08\text{mm}$,
Panel Thickness: 1.6mm;
- 4. Bottom Hole: $\text{Ø}6.0 \pm 0.08\text{mm}$,
Panel Thickness: 0.8-1.2mm.

Part No.	Part Name	Part No.	Part Name	A
41378	8G820V41378	42080	8G820V42080	4.8
41379	8G820V41379	42450	8G820V42450	6.4
41380	8G820V41380	42451	8G820V42451	7.9
41381	8G820V41381	42452	8G820V42452	9.5
41382	8G820V41382	42453	8G820V42453	12.7
42545	8G820V42545	42546	8G820V42546	15.9
41383	8G820V41383	42454	8G820V42454	19.1
Material: PA66 UL94 V2		Material: PA66 UL94 V0		

DREMEC Befestigungselemente GmbH						DATE	2020.03.19	DIMENSION	TOLERANCE
TITLE	CUPPED REVERSE LOCKING CIRCUIT BOARD SUPPORT					SCALE	FIT	L ≤ 4	±0.10
PART NAME	8G820V41378	MOLD NO.	S0418	DRAW	PLK	UNIT	MM	4 < L ≤ 15	±0.20
PART NO.	SEE TABLE	MATERIAL	SEE TABLE	DESIGN	PLK	VERSION	A0	15 < L ≤ 50	±0.30
DWG NO.	E4165	COLOR	SEE NOTES	APPROVAL	FDL	VIEW		50 < L ≤ 100	±0.40