



Product: [9539](#)

RS232, #24-9c, SR-PVC, O/A Foil, PVC Jkt, CMG

### Product Description

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

### Technical Specifications

#### Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | RS-232 Applications; Computer Communications; Low Voltage Analog Signals (4-20mA, 0-10V, ...); Low Voltage Digital Control (24V, ...); Line Level Audio; Panel Wiring |
|------------------------|---|

#### Construction Details

##### Conductor

| Element      | No. of Elements | Size   | Stranding | Material           |
|--------------|-----------------|--------|-----------|--------------------|
| Conductor(s) | 9               | 24 AWG | 7x32      | TC - Tinned Copper |

##### Insulation

| Element      | Material                                 | Nom. Thickness     | Nom. Insulation Diameter | Color Code  |
|--------------|--|--------------------|--------------------------|---|
| Conductor(s) | SR-PVC - Polyvinyl Chloride (Semi-Rigid) | 0.011 in (0.28 mm) | 0.044 in (1.1 mm)        | Black, White, Red, Green, Brown, Blue, Orange, Yellow, Purple |

##### Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 24 AWG (7x32) TC |

##### Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.032 in (0.81 mm) | 0.244 in (6.20 mm) |

Overall Cable Diameter (Nominal): 0.244 in (6.20 mm)

#### Electrical Characteristics

##### Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                   |
|--------------|--------------------|-------------------------------|---|--------------------------------|
| Conductor(s) | 25 Ohm/1000ft      | 30 pF/ft (98 pF/m)            | 55 pF/ft (180 pF/m)                             | 1.5 Amps per Conductor at 25°C |

##### Voltage

| UL Voltage Rating                |
|----------------------------------|
| 300 V (CMG), 300 V (UL AWM 2464) |

#### Mechanical Characteristics

##### Temperature

| UL Temperature                   | Operating      |
|----------------------------------|----------------|
| 60°C (UL CMG);80°C (UL AWM 2464) | -30°C to +80°C |

##### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 2.9 in (74 mm)  | 2.9 in (74 mm)    |

|                    |                |
|--------------------|----------------|
| Max. Pull Tension: | 55 lbs (25 kg) |
| Bulk Cable Weight: | 33 lbs/1000ft  |

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor (Not Riser or Plenum), Indoor  |
| Sustainability:                  | CA Prop 65  |
| Flammability / Reaction to Fire: | UL 1685 FT4 Loading, FT4, IEC 60332-1-2   |
| CPR Compliance:                  | CPR Euroclass: Eca; CPR UKCA Class: Eca   |
| NEC / UL Compliance:             | Article 800, CMG  |
| AWM Compliance:                  | AWM 2464  |
| CEC / C(UL) Compliance:          | CMG   |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark   |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)   |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.538 Revision Date: 04-19-2023 |
|----------------------|--|

## Part Numbers

### Variants

| Item #        | Color  | Putup Type | Length   | UPC/EAN       | Footnote |
|---------------|--------|------------|----------|---------------|----------|
| 9539.01U305   | Blue   | UnReel     | 305 m    | 8719605022066 |          |
| 9539.0030     | Chrome | Reel       | 30 m     | 8719605022011 |          |
| 9539 060100   | Chrome | Reel       | 100 ft   | 612825255406  |          |
| 9539.00U152   | Chrome | UnReel     | 152 m    | 8719605022028 |          |
| 9539.01152    | Chrome | Reel       | 152 m    | 8719605022042 |          |
| 9539.00U305   | Chrome | UnReel     | 305 m    | 8719605022035 |          |
| 9539.01305    | Chrome | Reel       | 305 m    | 8719605022059 |          |
| 9539 060500   | Chrome | Reel       | 500 ft   | 612825255420  | C        |
| 9539 060U500  | Chrome | UnReel     | 500 ft   | 612825255390  |          |
| 9539 0601000  | Chrome | Reel       | 1,000 ft | 612825255413  | C        |
| 9539 060U1000 | Chrome | UnReel     | 1,000 ft | 612825255383  |          |
| 9539 0605000  | Chrome | Reel       | 5,000 ft | 612825255437  |          |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.