

AUTO ACCESSORIES


NEW

HANDLEBAR MOUNT RACK

P/No. A13-229

Features:

- Easy to assemble. Handlebar mounted by screws
- Fixed bracket helps to stabilize the USB charger, socket and meter
- Surface mount model : A13-223
- **A13-229142C1-BB3**: ϕ 21mm receptacle with dust-proof cap
Rating: 12-24V DC 20A max.
- **A13-229194B2-BB3**: Dual USB charger with dust-proof cap
Input: 12-24V DC. Output: 5V 2.4A + 2.4A max, 2 ports.
- **A13-229230-BB3**: Dual USB charger with dust-proof cap
Input: 12-24V DC. Output: 5V 2.4A + 2.4A max, 2 ports.
Backlighting power indication shown per laser-engraving legend on panel.
- Size: ϕ 37.0 x 67.2 (D) mm



A13-229230-BB3

WATERPROOF MAGNETIC CAP FOR OUTLET USB & LIGHTER SOCKETS

P/No. A13-224

Features:

- Waterproof and dust-proof magnetic cap
- **A13-224A-BB3**: Dual USB charger with magnetic cap
Input: 12-24V DC. Output: 5V 2.4A + 2.4A max, 2 ports. IPX4
- **A13-224142C2-BB3**: ϕ 21mm receptacle with magnetic cap
Rating: 12-24V DC 20A max. IPX3
- **A13-224194B2-BB3**: Dual USB charger with magnetic cap
Input: 12-24VDC. Output: 5V 2.4A + 2.4A max, 2 ports. IPX3
- Size: 42.2 (W) x 56.2 (H) x 60.0 (T) mm



A13-224194B2-BB3

SINGLE HOLE PANEL

P/No. A13-226

Features:

- Plastic single hole panel, fitting by 2 screws
- Customized mark, printed on panel is available
- **A13-22665A-BB1**:
Input: 12V DC 20A max. A13-226-1A panel with snap in 12V outlet and cap
- **A13-226204B1-BB3**:
Input: 12/24V DC 20A max. A13-226-1B panel with snap in dual USB socket and cap
- **A13-226194B2-BB3**: Input: 12/24V DC. Output: 5V 2.4A+2.4A max.
A13-226-1C panel with screw in dual USB socket and cap.
- **A13-226142F-BB3**: Input: 12~24V DC, 20A max. A13-226-1C panel with ϕ 21mm receptacle and cap
- **A13-226220A1-BB3**: Input: 12~24V DC, 20A max. A13-226-1C panel with ϕ 12mm receptacle and cap
- **A13-226144-14-BB**: A13-226-1C panel with fitting hole fits with ϕ 12mm receptacle.
Mates with SCI model #A13-144 / 220 and 227 series.
- Size: 80.0 (W) x 45.0 (H) x 50.0 (T) mm



A13-226194B2-BB3

*All the specifications are subject to change without notice.



Headquarters:
TEL : 886-6-2532181
FAX : 886-6-2532633

Taipei Branch Office:
TEL : 886-2-25014062-4
FAX : 886-2-25040685

China Factory:
TEL : 86-752-3897988
FAX : 86-752-3897986
www.shinchin-sci.com

Hong Kong Branch:
TEL : 852-27939773
FAX : 852-27939830

Indonesia Factory:
TEL : 62-24-7627048
FAX : 62-24-7627047