





Ergonomic power plug

Technical data: acar P7

and effectiveness.

Maximum load	P _{MAX} 2300W
Nominal voltage U _N	230V
Nominal frequency	50Hz
Nominal load current	ΣI _N =10A MAX
Surge protection response time	<25ns
Maximum voltage U _C	250V 50Hz
Protection level U _P	≤1.3kV
Nominal discharge current i _N	2kA (L/N) – 8/20µs
Maximum discharge current i _{MAX}	6.5kA (L/N) – 8/20µs
Fuses	1 automatic fuse, slow blow 10A/250V
Anti-shock protection system	earthing pins connected to the protective earthing conductor
Number of socket outlets	5 two-pole socket outlets with earthing pin, 10A/250V 2 two-pole socket outlets without earthing, 2.5A/250V
Switch	illuminated double pole mains switch
Housing	made of self-extinguishing plastic
Dimensions	370x65x44mm
Weight	0.44kg

ize cables allowing for convenient and aesthetic management of

power cables extending from the **acar P7** to the appliances. Thus it allows to avoid messy cables under the desk, while protecting sensitive electrical equipment against surges and spikes. **acar P7** is equipped with an automatic fuse, which guarantees simplicity







ILLUMINATED DOUBLE POLE MAINS SWITCH AND SLOW-BLOW AUTOMATIC FUSE

5 SOCKET OUTLETS 10A WITH EARTHING PIN, 2 UNEARTHED EURO SOCKETS, ALL OF THEM WITH SAFETY SHUTTERS

USAGE OF THE CABLE MANAGEMENT SYSTEM

The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress. ATTENTION! The technical data define the maximum values of surges against which the device protects.