

Silicon-free distributor for the forms

Product used in plastic processing. Does not contain silicone. May be used in the manufacture of products requiring further surface treatment. The formulation may be used universally and is suitable for most plastic materials. Can be used as a lubricant or an antiadhesive agent. Does not build up in the mould and does not lead to the formation of deposits, allowing good surface quality by reducing defect count and improving performance. Operates at temperatures up to 170°C. Allows for subsequent painting or bonding without degreasing.

Application:

- as a lubricant or an antiadhesive agent,
- extrusion of plastic materials,
- vacuum-forming of plastics,
- injection moulding of plastic materials,
- manufacture of plastic laminates.

Physicochemical properties of the liquid:

Parameters	UoM	Result
Relative density at 20°C	g/cm ³	0,91
Viscosity	MPa·s	800-1400
Colour	-	colourless

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
400 ml	aerosol	4 / 24	ART.AGT-228

Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C / 122°F

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.