

# **XTAR D28 3600 Diving Flashlight**

Narrow beam dive light, a good partner for cave/wreck diving

- CREE XHP70.2 P4 LED, high efficiency lifespan
- Max output 3600lm, four brightness levels
- Runtime up to 2.5 hours at Turbo mode, with 4x18650 batteries
- Max beam throw 550m with focused beam angle 8°
- Press switch to turn on/off, easy to operate
- Power indicator and lock function for safe diving
- Anti-reverse circuit connection
- Solid 6N03 housing, anti-corrosion and anti-abrasion
- IPX8 waterproof, works well underwater 100m
- Smart temperature control

Max Output

**3600**lm

Four Brightness Levels



**Turbo**  
3600lm



**High**  
2000lm



**Mid**  
500lm



**Low**  
200lm

Runtime Up to **2.5**hrs at Turbo

Unflaggingly Light Up Sea World



2.5h

Turbo  
3600lm



4h

High  
2000lm



7.5h

Mid  
500lm



16h

Low  
200lm





Max Throw **550m** / **8°** Focused Beam Angle

This light can penetrate the darkness and allows users to see deeper and sense potential hazards



**CREE XHP**  
**70.2 P4 LED**

**High efficiency**  
**Lifespan>20000hrs**

This dive light emits consistent color that greatly strengthen its reliability in the sea world.





## Easy to Get Start

Press switch to turn on

Press switch repeatedly swap among 4 brightness levels

Long press switch to power off



## Power Indicator

100%~30% Solid Green

30%~1% Solid Red

<1% Blinking Red

## Lock Function

This greatly helps in prevention of accidental switch-on or sudden disappearing of lights



## Anti-reverse circuit connection

It is safe to place battery's positive and negative electrodes reversely by accident.

## Solid 6N03 housing

Constructed from solid 6N03 and has a class III hard coat anodized finish. Anti-corrosion, anti-abrasion



## IPX8 Waterproof

It works fine within 100m depth underwater.





## Smart Temperature Control

When temperature within rises up to about 70°C, it will automatically reduce the brightness. Thus promises longer life.

## Flexible in Use

The light supports use of lanyard attachment or handle, more convenience for your underwater journey.

Note: handle is not included in the package.



## Parameters

Model	D28 3600			
ANSI	Turbo	High	Mid	Low
Lumens	3600	2000	500	200
Runtime	2.5hr	4hr	7.5hr	16hr
Beam Throw	550m			
Beam Angle	8°			
Max. Intensity	75625cd			
Color Temperature	7000K (Cool White)			
IPX8	Underwater 100m			
Size	Φ84(Head)*Φ50(Body)*Φ57.5(Tail), Overall Length 191.5mm			
Net Weight	396g			

Notes:

- 1.Above-mentioned runtime (tested by four XTAR 18650 Li-ion batteries in the case of 25°C water-cooling) are approximate and may differ depending on battery and environment.
- 2.Working voltage: 11~16.4V
- 3.Batteries: 4\*18650 Li-ion protected batteries