



**DACO SEMICONDUCTOR CO., LTD.**

**DACSB60060CT**

## SiC SCHOTTKY DIODE TYPE 2x300A

### Features

- High surge current capable
- Zero reverse recovery current
- High bandwidth
- Temperature Independent Switching Behavior
- V<sub>DC</sub> 600 V
- I<sub>F</sub> (T<sub>C</sub><135°C) 2x300 A

### Benefits

- Unipolar rectifier
- Zero switching loss
- Higher efficiency
- Smaller heat sink
- Parallel devices without thermal runaway


### Applications

- Motor drives
- Switch mode power supplies
- EV chargers
- Solar inverters
- Welding equipment
- Power factor correction
- Diode snubber
- Automotive
- Induction heating

Preliminary



Dimensions in mm (1 mm = 0.0394")





### Maximum Ratings

Operating Junction Temperature : -55 °C to +175 °C

Storage Temperature : -55 °C to +175 °C

Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum DC Blocking Voltage
DACSB60060CT	600V	600V

Maximum Rating	Symbol	Conditions	Value	Unit
Continuous forward current (per leg)	I <sub>F</sub>	T <sub>C</sub> =135 °C	300	
Surge non-repetitive forward current sine halfwave (per leg)	I <sub>FSM</sub>	T <sub>C</sub> =25 °C, t <sub>p</sub> =8.3 ms	2000	A
		T <sub>C</sub> =150 °C, t <sub>p</sub> =8.3 ms	1250	
Non-repetitive peak forward current (per leg)	I <sub>F,max</sub>	T <sub>C</sub> =25 °C, t <sub>p</sub> =10 μs	8000	
		T <sub>C</sub> =150 °C, t <sub>p</sub> =10 μs	5000	
Repetitive peak reverse voltage	V <sub>RRM</sub>	T <sub>J</sub> =25 °C	600	V
Mounting torque		M6 Screw	3~4.7	N-m





DACO SEMICONDUCTOR CO., LTD.

DACSB60060CT

**Electrical Characteristics**, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified. (per leg)






Static Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
DC blocking voltage	$V_{DC}$		600	-	-	
Diode forward voltage	$V_F$	$I_F=200A, T_j=25\text{ }^\circ\text{C}$	-	1.45	1.65	V
		$I_F=200A, T_j=175\text{ }^\circ\text{C}$	-	1.70	2.00	
Reverse current	$I_R$	$V_R=600V, T_j=25\text{ }^\circ\text{C}$	-	40	200	$\mu\text{A}$
		$V_R=600V, T_j=175\text{ }^\circ\text{C}$	-	200	1,000	

**AC Characteristics** (per leg)

Static Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Total capacitive charge	$Q_{rr}$	$V_R=400V, T_j=25\text{ }^\circ\text{C}$	-	988	-	nC
Total capacitance	C	$V_R=0V, f=1\text{ MHz}$ $T_j=25\text{ }^\circ\text{C}$	-	17,800	-	pF
		$V_R=200V, f=1\text{ MHz}$ $T_j=25\text{ }^\circ\text{C}$	-	1,769	-	
		$V_R=400V, f=1\text{ MHz}$ $T_j=25\text{ }^\circ\text{C}$	-	1,655	-	

**Thermal Characteristics** (per leg)

Static Characteristics	Symbol	Values	Unit
		typ.	
Thermal resistance from junction to case	$R_{\theta JC}$	0.056	°C/W

**Typical Performance****Forward Characteristics** (parameterized on  $T_j$ )**Reverse Characteristics** (parameterized on  $T_j$ )**Capacitance****Current Derating****Recovery Charge****Forward Surge Current**