

1200VA UPS "Home"

EG-UPS-H1200

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.04123
Crtn weight, kgs	18.73
Individual package size LxWxH:	369x161x290 mm
Carton size LxWxH:	380x350x310 mm
Country of origin	CN
Barcode	8716309126342
Customs code	8504408590

Package contents

UPS
User manual

Specifications

UPS type: line interactive
 Input: AC 162 ... 295 Vac, 50Hz/60Hz ±10%
 Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
 Switching time: no more than 10 ms
 Backup time: up to .20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/7Ah x 2 pc

Charge time: up to 8 hours
 Sockets: 4 x Schuko output (CEE 7/4)
 Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing
 Noise level: up to 45 dB (1 m distance)

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

