

Online UPS, 2000 VA

EG-UPSO-2000

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Specifications

allowed

VDC)

Output power factor: 0.9

Switching time: zero

UPS type: online, pure sine wave

Input: 220V AC ± 25%, 50Hz / 60Hz ± 10%

Output: 220V AC ± 1%, 50Hz / 60Hz ± 0.5% (on battery)

Inverter output efficiency (resistive load): 85%, any load type is

Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 7 Ah x 6 pcs (72

Features

- Online type UPS: double voltage conversion without switching the power
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code

0.061404 23.18 510x280x430 mm 510x280x430 mm CN 8716309124829 8504408590

Package contents

UPS Power cord USB cable Software CD Spare fuse

External battery connectors: yes System requirements In order to work correcity, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Backup time: 8...20 mins (depends on the load)

Charge time: 90% capacity restored in 3 hours

Certificates



Copyright © 2009–2023, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588

www.energenie.com | postmaster@energenie.com