

EVGK busbar fork, 3-phase, L1 - L2 - L3, shortenable version with end caps included, 6 module units, 10 mm²



Part no. EVGK-3PHAS/6MODUL

EP-501075

**EL Number
(Norway)**

1604095

General specifications		
Product name		Eaton Moeller series busbar
Part no.		EVGK-3PHAS/6MODUL
EAN		9010653035190
Product Length/Depth		106 millimetre
Product height		28.5 millimetre
Product width		15 millimetre
Product weight		0.036 kilogram
Certifications		CE
Product Tradename		None
Product Type		Busbar
Product Sub Type		None
Product Specification Details		
Color		Grey
Cross section		10 mm ²
EL number		1604095
Electric connection type		Fork
Features		Insulated Can be cut to size
Number of modular spacings		6
Number of phases		3
Number of poles		Three-pole
Pitch dimensions		17.8 mm
Rated conditional short-circuit current (I _q)		25 kA
Rated operating voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I _u)		63 A
Suitable for		2 devices

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011])			
Number of phases			3
Number of poles			3
Suitable for number of devices			2
Module width		mm	17.8
Cross section		mm ²	10
Length		mm	106
Width in number of modular spacings			6
Rated permanent current I _u		A	63
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	4
Conditioned rated short-circuit current I _q		kA	25
Max. rated operation voltage U _e		V	415
Rated short-time withstand current I _{cw}		kA	0

Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Grey