

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 1178 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

IPD Click - TPD2015





PID: MIKROE-6074

IPD Click is a compact add-on board for controlling inductive and resistive loads in industrial automation and other demanding applications. This board features the TPD2015FN, an 8-channel high-side switch with MOSFET outputs from <u>Toshiba Semiconductor</u>. This component is directly compatible with CMOS and TTL logic, making it ideal for driving motors, lamps, and industrial programmable logic controllers. It has protection against overcurrent and overheating, ensuring system stability and safety under various operating conditions, supports loads up to 50mH with a current capacity of 0.5A per channel, and accepts an external power supply ranging from 8-24V. It offers flexible integration options with inputs for direct output control, load decoupling diodes, and pre-configured jumpers for easy setup. This Click board ™ is the perfect solution for developers seeking reliable load management in factory automation, industrial control systems, and similar applications.

IPD Click is fully compatible with the mikroBUS[™] socket and can be used on any host system supporting the mikroBUS[™] standard. It comes with the mikroSDK open-source libraries, offering unparalleled flexibility for evaluation and customization. What sets this <u>Click board</u> apart is the groundbreaking <u>ClickID</u> feature, enabling your host system to seamlessly and automatically detect and identify this add-on board.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Specifications

Туре	Relay
Applications	Ideal for developing wearable technology, smart home devices, robotics, and AR/VR applications
On-board modules	TPD2015FN - 8-channel high-side load switch featuring MOSFET outputs from Toshiba Semiconductor
Key Features	High-side load switch, CMOS/TTL logic control, protection features, suitable for inductive and resistive loads, inductive load of 50mH max, 0.5A output current per channel, can drive load directly, high-voltage operation, and more
Interface	GPIO
ClickID	Yes
Compatibility	mikroBUS™
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V or 5V,External

Resources

<u>mikroBUS™</u>

mikroSDK

Click board™ Catalog

Click boards™

Downloads

TPD2015FN datasheet

CRS20I40A datasheet

IPD Click - TPD2015 click 2D and 3D files

IPD Click - TPD2015 schematic

IPD Click - TPD2015 example on Libstock

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.

ISO 27001: 2013 certification of informational





health and safety management system.