



FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

Part Number: LAS1Y- 11Y/◇/JC

"◇"	Operation position
2	Two Position

**SPECIFICATIONS:**

- 1.Switch Rating: AC220V/2A, DC220V/0.1A.
- 2.Mechanical Life: ≥500,000cycles.
- 3.Electrical Life: ≥50,000cycles.
- 4.Contact Resistance: ≤50mΩ.
- 5.Insulation Resistance: ≥100MΩ.
- 6.Dielectric Strength:  
Between terminals of the same pole: AC 1,500V, RMS 50Hz, 1min;  
Between terminals of different pole: AC 2,000V, RMS 50Hz, 1min.
- 7.Operating Temperature: -25°C ~ +55°C(No Freezing).
- 8.IP Class: IP40.
- 9.Terminal Type: Pin Terminal(2.8 x 0.5mm).

**MATERIALS:**

- 1.Contact: Silver alloy.
- 2.Button: PC.
- 3.Body: PC.
- 4.Base: PC.

BRAND 品牌 <b>ONPOW</b>	红波按钮制造有限公司 ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.			
	USED 用途	APPD 审核	CH	2020/05/03
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.	FINISH 处理	CHKD 校对	NCH	2020/05/03
	SCALE 比例	UNIT 单位	DR. 制图	ZPD 2020/05/03
DIMENSIONS	TOLERANCE	TITLE 名称	LAS1 Series Pushbutton Switches	
0.00 TO 18.00mm	±0.43mm	DWG NO. 图号	LAS1Y- 11Y-JC	
18.01 TO 30.00mm	±0.52mm	FILE NAME 档案名称	LAS1-Y.DWG	SHEET 张
30.01 TO 50.00mm	±0.62mm			1 / 1
50.01 TO 80.00mm	±0.74mm			REV. 更改
				1