


**Product:** [MRG1791](#) 



MRG1791 - Analog Video, RG179 Type, 30 AWG Stranded SCCS, 85% TC Braids, PVC Jkt

## Product Description

Analog Video, RG179 Type, 30 AWG Stranded Silver Copper Covered Steel Conductor, 85% Tinned Copper Braid Shield, PVC Jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Standard analog video
------------------------	-----------------------

### Construction Details

RG Type:	179
----------	-----

#### Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	30 AWG	Stranded	0.3 mm	SCCS - Silvered Copper Covered Steel

#### Insulation

Element	Material	Nom. Insulation Diameter
Insulated Conductor	PE - Polyethylene	1.6 mm (0.063 in)

#### Outer Shield

Outer Shield Type	Material	Coverage
Braid	Tinned Copper (TC)	85%

#### Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	2.8 mm

Table Notes:	According to EN 50290-2-20
--------------	----------------------------

### Electrical Characteristics

Regularity of Impedance:	Min. 40 dB
--------------------------	------------

#### Attenuation

Frequency	Nom. Attenuation
10 MHz	15 dB/100m
100 MHz	27 dB/100m
1000 MHz	85 dB/100m

#### Electricals

Max. Conductor DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
802 Ohm/km (244 Ohm/1000ft)	67 pF/m (20 pF/ft)	75 Ohm	66%

#### Voltage

Voltage Rating
2000 V DC / 1000 V RMS

### Mechanical Characteristics

## Temperature

Operating	Installation	Storage
-25°C To +70°C	-5°C To +50°C	-25°C To +70°C

## Standards and Compliance

Environmental Suitability:	Indoor/Outdoor
CPR Compliance:	CPR Euroclass: Fca
Military Compliance:	MIL-C-17
European Directive Compliance:	EU CE Mark

## History

Update and Revision:	Revision Number: 0.195 Revision Date: 12-22-2023
----------------------	--

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	EAN
MRG1791.0050	Black	Reel	50 m	8719605102935
MRG1791.00100	Black	Reel	100 m	8719605102928
MRG1791.00150	Black	Reel	150 m	8719605162977

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.