


■Features

- This flexible LED filament is extremely soft and can be bent and folded into different shapes at will
- There are 100pcs of microscopic LED lights inside the rubberized, colorful silicone outer shell
- Operating on DC3V, it emits full-angle 360° light.
- IP Rate: IP20


■Applications

- Indirect accent décor light
- Substitute neon light
- Dioramas
- Dollhouses
- DIY lighting decoration


Product Picture



Outline Dimension




Circuit Diagram



■Typical Performance (Ta=25°C)

Item	Symbol	Min.	Typ.	Max.	Unit
LED Module Power	Pm	-	0.9	1.12	W
Input Voltage(DC)	Vi	-	3.0	3.3	V
Input Current	If	-	0.3	0.35	A
Beam Pattern	BP	-	360	-	Deg
Operating Temperature	Topr	-10	-	40	°C
Storage Temperature	Tstg	-30	-	55	°C
LED Quantity	QTY	-	100	-	PCS
Total Length	Lmod.	-	130	-	mm

■Directivity



■Device Selection Guide

Item No.	Color	CCT(K) / WD(nm)	Luminous Flux / String (Typ.)
OSFX1301AW4-3V	White	6000-8500K	100 lm
OSFX1301AK3-3V	Pink	x:0.39-0.43, y:0.19-0.23	70 lm
OSFX1301AB4-3V	Blue	450-460nm	12 lm
OSFX1301AG7-3V	Yellow Green	555-565nm	135 lm
OSFX1301AY5-3V	Yellow	585-595nm	97 lm
OSFX1301AR4-3V	Red	610-620nm	22 lm