



## + INFORMATION

- + High quality flame-retardant insulation tape
- + Extremely flexible with good adhesion
- + Available in a full range of colours

## + PROPERTIES

**Storage Temperature**

Below 21°C a 50% R.H

**Material**

PVC, natural rubber adhesive

**Conforms to**

BS EN 60454-1, BS EN 60454-2 and BS EN 60454-3.1

**Packaging**

pack of 10

**Available Colours**

Black, Red, Yellow, Blue. Green, White, Grey, Brown and Earth(Green/Yellow)

## + PROPERTY

PROPERTY	VALUE	TEST METHOD
TOTAL THICKNESS	0.15mm	GB7125-1999
ELONGATION	≥160%	GB7753-1987
PEEL ADHESION	≥1.5N/cm	GB2792-1998
TENSILE STRENGTH	≥20N/cm	GB7753-1987
FLAMMABILITY	<=10 seconds	UL510
VOLTAGE BREAKDOWN	7Kv	GBT4850-2002
APPLICATION TEMP	≥80°C	GBT7752-1987

## + ORDERING INFORMATION

PART NUMBER	REEL LENGTH (METRES)	TAPE WIDTH (mm)
IT1 *	20	19

\* specify colour when ordering: Black, Red, Yellow, Blue, Green, White, Grey, Brown and Earth (Green/Yellow)