

**zameL**

**BISTABLE  
RELAY**

**PBP-04**

**230 V AC**

**exta**

Protection degree IP20

Bistable lighting control

[www.zamel.com](http://www.zamel.com)

## WARRANTY CARD

There is a 24 month guarantee on the product

1. ZAMEL Sp. z o.o. assures a 24 month guarantee for the product.
2. The manufacturer's guarantee does not cover any of the following actions:
  - a) mechanical damage during transport, loading / unloading or under other circumstances,
  - b) damage caused by incorrect product mounting or misuse,
  - c) damage caused by unauthorised modifications made by the PURCHASER or any third parties to the product or any other devices required for the product functioning,
  - d) damage caused by Act of God or any other incidents independent of the manufacturer – ZAMEL Sp z o.o.
3. The PURCHASER shall lay any claims in writing in the place of purchase or to ZAMEL Sp. z o.o.
4. ZAMEL Sp. z o.o. is liable for processing any claim according to current Polish legislation.
5. ZAMEL Sp. z o.o. shall process the claim at its own discretion: product repair, replacement or money return.
6. The manufacturer's guarantee is valid in the Republic of Poland.
7. The PURCHASER's statutory rights in any applicable legislation whether against the retailer arising from the purchase contract or otherwise are not affected by this warranty.

Salesman stamp and signature,  
date of sale

# zameL

ZAMEL sp. z o.o.  
43-200 Pszczyna, ul. Zielona 27; tel.: (32) 210 46 65; fax: (32) 210 80 04  
e-mail: [marketing@zamel.pl](mailto:marketing@zamel.pl), [www.zamel.com](http://www.zamel.com)

## BISTABLE RELAY PBP-04

**It is designed to control lighting  
or any other device**

- Bistable control of lighting or any other device,
- cooperation with mono modular push-buttons with backlight,
- control possibility from different places,
- double-wire control installation,
- system release only by means of line L,
- load switching indicator - LED red,
- voltage relay output - 1 NO (normal closed) contact with max. capacity of 10A,
- operating temperature range: from  $-20 \pm +45$  °C,
- dimensions: 47,5 x 47,5 x 20 mm.

**230 V AC; 50 Hz; 0,2 W; IP20**

PN-EN 60669-1, PN-EN 60669-2-1  
PN-EN 61000-4-2,3,4,5,6,11



**Made in Poland**



The symbol means selective collecting of electrical and electronic equipment. It is forbidden to put the used equipment together with other waste.

Declaration of Conformity is at [www.ledix.pl](http://www.ledix.pl)