

Data Sheet

Battery Control

Item-no.: 67301000 (BP)

Item-no.: 67301100 (SP)

03.06.2015

Benable Plug

Tension range: 8 Ampere
Fuse: 8 Ampere
Connectores: screw-type

Housing: ABS
temperature load: max. 110°C
Connector spring : Cu Sn 6
Surface : bright pickled
Contact spring: Cu Zn 37 F45
Oberfläche: gal. Ni 5
Plug Pin: Cu Zn 40 Pb 2
Surface gal. Ni 5

Material Conector:

Housing: Novodur
temperature load: max. 110°C
Negative terminal: Cu Zn 36 F44
Positive terminal: MS below nickel plated 3µ tinned

Cable:

Cross section: 2 x 0,75 mm²
length: 1 m

Battery Control

Item-no.: 67301000 (BP)

Item-no.: 67301100 (SP)

03.06.2015

Electronic:

Nominal voltage: 12 V/DC

Switch-On voltage: $12,3 \pm 0,2$ V/DC

Switch-Off voltage : $11,0 \pm 0,2$ V/DC

Operating Current: 8 A

Internal Consumption Relais

-on: 20 mA

-off 5 mA

Temperature area : -20 bis +70 °C

Overload protection: 10 A

Differential protection yes

Reset after short circuit: Plug 5 seconds unplug and plug in again

