

Three Phase Half Controlled Bridges


PSDH 110

I_{dAV} = 110 A
 V_{RRM} = 400-1600 V

Preliminary Data Sheet

V_{RSM}	V_{RRM}	Type
V_{DSM}	V_{DRM}	
500	400	PSDH 110/04
900	800	PSDH 110/08
1300	1200	PSDH 110/12
1500	1400	PSDH 110/14
*1700	*1600	PSDH 110/16

* Delivery on request



Symbol	Test Conditions	Maximum Ratings
I_{dAV}	$T_C = 85^\circ C$	per module 110 A
I_{TSM}, I_{FSM}	$T_{VJ} = 45^\circ C$	$t = 10$ ms (50 Hz), sine 1150 A
	$V_R = 0$	$t = 8.3$ ms (60 Hz), sine 1230 A
	$T_{VJ} = T_{VJM}$	$t = 10$ ms (50 Hz), sine 1000 A
	$V_R = 0$	$t = 8.3$ ms (60 Hz), sine 1070 A
$\int i^2 dt$	$T_{VJ} = 45^\circ C$	$t = 10$ ms (50 Hz), sine 6600 $A^2 s$
	$V_R = 0$	$t = 8.3$ ms (60 Hz), sine 6280 $A^2 s$
	$T_{VJ} = T_{VJM}$	$t = 10$ ms (50 Hz), sine 5000 $A^2 s$
	$V_R = 0$	$t = 8.3$ ms (60 Hz), sine 4750 $A^2 s$
$(di/dt)_{cr}$	$T_{VJ} = T_{VJM}$	repetitive, $I_T = 50$ A 150 $A/\mu s$
	$f = 400$ Hz, $t_p = 200$ μs	
	$V_D = 2/3 V_{DRM}$	
$(dv/dt)_{cr}$	$I_G = 0.3$ A	non repetitive, $I_T = 1/3 \cdot I_{dAV}$ 500 $A/\mu s$
	$di_G/dt = 0.3$ $A/\mu s$	
$(dv/dt)_{cr}$	$T_{VJ} = T_{VJM}$	$V_{DR} = 2/3 V_{DRM}$ 1000 $V/\mu s$
	$R_{GK} = \infty$, method 1 (linear voltage rise)	
P_{GM}	$T_{VJ} = T_{VJM}$	$t_p = 30$ μs ≤ 10 W
	$I_T = I_{TAVM}$	$t_p = 500$ μs ≤ 5 W
P_{GAVM}		0.5 W
V_{RGM}		10 V
T_{VJ}		-40 ... + 125 $^\circ C$
T_{VJM}		125 $^\circ C$
T_{stg}		-40 ... + 125 $^\circ C$
V_{ISOL}	50/60 HZ, RMS	$t = 1$ min 2500 V ~
	$I_{ISOL} \leq 1$ mA	$t = 1$ s 3000 V ~
M_d	Mounting torque (M6)	5 Nm
	Terminal connection torque (M6)	5 Nm
Weight	typ.	270 g

Features

- Package with screw terminals
- Isolation voltage 3000 V~
- Planar glasspassivated chips
- Low forward voltage drop
- UL registered, E 148688

Applications


- Heat and temperature control for industrial furnaces and chemical processes
- Lighting control
- Motor control
- Power converter

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability
- High power density

Package, style and outline

Dimensions in mm (1mm = 0.0394")



Symbol	Test Conditions	Characteristic Value			
I_D, I_R	$T_{VJ} = T_{VJM}, V_R = V_{RRM}, V_D = V_{DRM}$	\leq	5	mA	
V_T	$I_T = 200A, T_{VJ} = 25^\circ C$	\leq	1.75	V	
V_{TO}	For power-loss calculations only ($T_{VJ} = T_{VJM}$)		0.85	V	
r_T			6	m Ω	
V_{GT}	$V_D = 6V$	$T_{VJ} = 25^\circ C$	\leq	1.5	V
		$T_{VJ} = -40^\circ C$	\leq	1.6	V
I_{GT}	$V_D = 6V$	$T_{VJ} = 25^\circ C$	\leq	100	mA
		$T_{VJ} = -40^\circ C$	\leq	200	mA
V_{GD}	$T_{VJ} = T_{VJM} \quad V_D = 2/3 V_{DRM}$	\leq	0.2	V	
I_{GD}	$T_{VJ} = T_{VJM} \quad V_D = 2/3 V_{DRM}$	\leq	5	mA	
I_L	$T_{VJ} = 25^\circ C, t_p = 30\mu s$	\leq	450	mA	
	$I_G = 0.3A, di_G/dt = 0.3A/\mu s$				
I_H	$T_{VJ} = 25^\circ C, V_D = 6V, R_{GK} = \infty$	\leq	200	mA	
t_{gd}	$T_{VJ} = 25^\circ C, V_D = 1/2 V_{DRM}$	\leq	2	μs	
	$I_G = 0.3A, di_G/dt = 0.3A/\mu s$				
t_q	$T_{VJ} = T_{VJM}, I_T = 20A, t_p = 200\mu s, V_R = 100V$		150	μs	
	$-di/dt = 10A/\mu s, dv/dt = 15V/\mu s, V_D = 2/3 V_{DRM}$				
R_{thJC}	per thyristor; sine 180°el		0.65	K/W	
	per module		0.108	K/W	
R_{thJK}	per thyristor; sine 180° el		0.8	K/W	
	per module		0.133	K/W	
d_s	Creeping distance on surface		10.0	mm	
d_A	Creeping distance in air		9.4	mm	
a	Max. allowable acceleration		50	m/s ²	




Fig. 1 Forward current vs. voltage drop per diode or thyristor




Fig. 2 Gate trigger delay time




Fig. 3 Surge overload current per diode (or thyristor) I_{FSM} , I_{TSM} : Crest value t : duration




Fig.4 Gate trigger characteristic




Fig.5 Maximum forward current at case temperature




Fig.6 Transient thermal impedance per thyristor or diode (calculated)




Fig. 7 Power dissipation vs. direct output current and ambient temperature