

SEMiX453GAL17E4p



SEMiX® 3p

Trench IGBT Modules

SEMiX453GAL17E4p

Features*


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- Press-fit pins as auxiliary contacts
- UL recognized, file no. E63532

Typical Applications

- AC inverter drives
- UPS
- Renewable energy systems

Remarks

- Product reliability results are valid for $T_j=150^\circ\text{C}$
- V_{isol} between temperature sensor and power section is only 2500V
- For storage and case temperature with TIM see document "TP(*) SEMiX 3p"



GAL

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V_{CES}	$T_j = 25^\circ\text{C}$		1700	V
I_C	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	697	A
		$T_c = 80^\circ\text{C}$	530	A
I_{Cnom}			450	A
I_{CRM}			1350	A
V_{GES}			-20 ... 20	V
t_{psc}	$V_{CC} = 1000\text{ V}$ $V_{GE} \leq 15\text{ V}$ $V_{CES} \leq 1700\text{ V}$	$T_j = 150^\circ\text{C}$	10	μs
T_j			-40 ... 175	$^\circ\text{C}$
Inverse diode				
V_{RRM}	$T_j = 25^\circ\text{C}$		1700	V
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	557	A
		$T_c = 80^\circ\text{C}$	412	A
I_{FRM}			900	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$		2565	A
T_j			-40 ... 175	$^\circ\text{C}$
Freewheeling diode				
V_{RRM}	$T_j = 25^\circ\text{C}$		1700	V
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	557	A
		$T_c = 80^\circ\text{C}$	412	A
I_{FRM}			900	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$		2565	A
T_j			-40 ... 175	$^\circ\text{C}$
Module				
$I_{t(RMS)}$			600	A
T_{stg}	module without TIM		-40 ... 125	$^\circ\text{C}$
V_{isol}	AC sinus 50Hz, $t = 1\text{ min}$		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
$V_{CE(sat)}$	$I_C = 450\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	1.90	2.20		V
		$T_j = 150^\circ\text{C}$	2.31	2.60		V
V_{CE0}	chipelevel	$T_j = 25^\circ\text{C}$	1.10	1.20		V
		$T_j = 150^\circ\text{C}$	1.00	1.10		V
r_{CE}	$V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	1.78	2.2		$\text{m}\Omega$
		$T_j = 150^\circ\text{C}$	2.9	3.3		$\text{m}\Omega$
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 18\text{ mA}$		5.2	5.8	6.4	V
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1700\text{ V}, T_j = 25^\circ\text{C}$				5	mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$		35.4		nF
C_{oes}		$f = 1\text{ MHz}$		1.29		nF
C_{res}		$f = 1\text{ MHz}$		1.14		nF
Q_G	$V_{GE} = -8\text{ V...} + 15\text{ V}$			3600		nC
R_{Gint}	$T_j = 25^\circ\text{C}$			1.7		Ω

SEMiX453GAL17E4p



SEMiX® 3p

Trench IGBT Modules

SEMiX453GAL17E4p

Features*

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- Press-fit pins as auxiliary contacts
- UL recognized, file no. E63532


Typical Applications

- AC inverter drives
- UPS
- Renewable energy systems

Remarks

- Product reliability results are valid for $T_j=150^\circ\text{C}$
- V_{isol} between temperature sensor and power section is only 2500V
- For storage and case temperature with TIM see document "TP(*) SEMiX 3p"

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
IGBT					
$t_{d(on)}$	$V_{CC} = 900\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	290		ns
t_r	$I_C = 450\text{ A}$	$T_j = 150\text{ }^\circ\text{C}$	90		ns
E_{on}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	131		mJ
	$R_{G\ on} = 2.7\ \Omega$	$T_j = 150\text{ }^\circ\text{C}$	790		ns
$t_{d(off)}$	$R_{G\ off} = 2.7\ \Omega$	$T_j = 150\text{ }^\circ\text{C}$	175		ns
t_f	$di/dt_{on} = 4600\text{ A}/\mu\text{s}$	$T_j = 150\text{ }^\circ\text{C}$	146		mJ
	$di/dt_{off} = 2300\text{ A}/\mu\text{s}$	$T_j = 150\text{ }^\circ\text{C}$			
E_{off}	$dv/dt = 3200\text{ V}/\mu\text{s}$	$T_j = 150\text{ }^\circ\text{C}$			
	$L_s = 21\text{ nH}$				
$R_{th(j-c)}$	per IGBT			0.06	K/W
$R_{th(c-s)}$	per IGBT ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)		0.029		K/W
$R_{th(c-s)}$	per IGBT, pre-applied phase change material		0.02		K/W
Inverse diode					
$V_F = V_{EC}$	$I_F = 450\text{ A}$	$T_j = 25\text{ }^\circ\text{C}$	1.98	2.37	V
	$V_{GE} = 0\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	2.12	2.52	V
	chipelevel				
V_{F0}	chipelevel	$T_j = 25\text{ }^\circ\text{C}$	1.32	1.56	V
		$T_j = 150\text{ }^\circ\text{C}$	1.08	1.22	V
r_F	chipelevel	$T_j = 25\text{ }^\circ\text{C}$	1.46	1.80	m Ω
		$T_j = 150\text{ }^\circ\text{C}$	2.3	2.9	m Ω
I_{RRM}	$I_F = 450\text{ A}$	$T_j = 150\text{ }^\circ\text{C}$	380		A
Q_{rr}	$di/dt_{off} = 4850\text{ A}/\mu\text{s}$	$T_j = 150\text{ }^\circ\text{C}$	120		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	72		mJ
	$V_{CC} = 900\text{ V}$				
$R_{th(j-c)}$	per diode			0.1	K/W
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)		0.048		K/W
$R_{th(c-s)}$	per diode, pre-applied phase change material		0.038		K/W
Freewheeling diode					
$V_F = V_{EC}$	$I_F = 450\text{ A}$	$T_j = 25\text{ }^\circ\text{C}$	1.98	2.37	V
	$V_{GE} = 0\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	2.11	2.52	V
	chipelevel				
V_{F0}	chipelevel	$T_j = 25\text{ }^\circ\text{C}$	1.32	1.56	V
		$T_j = 150\text{ }^\circ\text{C}$	1.08	1.22	V
r_F	chipelevel	$T_j = 25\text{ }^\circ\text{C}$	1.46	1.80	m Ω
		$T_j = 150\text{ }^\circ\text{C}$	2.3	2.9	m Ω
I_{RRM}	$I_F = 450\text{ A}$	$T_j = 150\text{ }^\circ\text{C}$	380		A
Q_{rr}	$di/dt_{off} = 4850\text{ A}/\mu\text{s}$	$T_j = 150\text{ }^\circ\text{C}$	120		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150\text{ }^\circ\text{C}$	72		mJ
	$V_{CC} = 900\text{ V}$				
$R_{th(j-c)}$	per diode			0.1	K/W
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)		0.048		K/W
$R_{th(c-s)}$	per diode, pre-applied phase change material		0.038		K/W



GAL

SEMiX453GAL17E4p



SEMiX® 3p

Trench IGBT Modules

SEMiX453GAL17E4p

Features*

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- Press-fit pins as auxiliary contacts
- UL recognized, file no. E63532


Typical Applications

- AC inverter drives
- UPS
- Renewable energy systems

Remarks

- Product reliability results are valid for $T_j=150^\circ\text{C}$
- V_{isol} between temperature sensor and power section is only 2500V
- For storage and case temperature with TIM see document "TP(*) SEMiX 3p"

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Module						
L_{CE}				20		nH
$R_{CC'+EE'}$	measured per switch	$T_C = 25^\circ\text{C}$		0.95		m Ω
		$T_C = 125^\circ\text{C}$		1.25		m Ω
$R_{th(c-s)1}$	calculated without thermal coupling			0.009		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module ($\lambda_{grease}=0.81\text{ W/(m}^2\text{K)}$)			0.014		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, pre-applied phase change material			0.021		K/W
M_s	to heat sink (M5)		3		6	Nm
M_t		to terminals (M6)	3		6	Nm
						Nm
w					350	g
Temperature Sensor						
R_{100}	$T_C=100^\circ\text{C}$ ($R_{25}=5\text{ k}\Omega$)			$493 \pm 5\%$		Ω
$B_{100/125}$	$R(T)=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$;			$3550 \pm 2\%$		K



GAL




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature $I_c = f(T_c)$




Fig. 3: Typ. turn-on /-off energy = $f(I_c)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. $R_{CC+EE'}$




Fig. 11: Typ. CAL diode peak reverse recovery current





Fig. 12: Typ. CAL diode recovery charge


SEMiX453GAL17E4p

Package outline

	0,3 connector 3-4/10-11
	0,2 each single connector A



PCB drillhole pattern




Dimensions in mm

Dimensions valid in mounted status

1)

PCB hole specification see Mounting Instructions SEMiX press-fit

SEMiX 3p



pinout

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.