

Product data sheet

Specifications



cartridge M200 - 2 analog current outputs

TMCR2AQ2C

Main

Range of product	Easy Modicon M200
Product or component type	Analogue output cartridge
Product compatibility	Easy Modicon M200

Complementary

Analogue output number	2
Analogue output type	Current: 4...20 mA
Analogue output resolution	12 bits
LSB value	3.91 μ A 4...20 mA current
Load type	Resistive
Load impedance ohmic	\leq 500 Ohm
Conversion time	20 ms
Stabilisation time	40 ms
Absolute accuracy error	+/- 1 % of full scale +/- 0.3 % of full scale at 25 °C
Temperature drift	+/- 0.02 %FS/°C
Repeat accuracy	+/- 0.4 %FS
Non-linearity	+/- 0.01 %FS
Cross talk	\leq 1 LSB
Type of cable	Twisted shielded pairs cable
Electrical connection	3 x 1.5 mm ² 2 screw terminal blocks with pitch 3.81 mm adjustment for outputs
Maximum cable distance between devices	Twisted shielded pairs cable: <30 m for output
Insulation	Non-insulated between analogue output and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Net weight	0.012 kg

Environment

Immunity to microbreaks	10 ms
-------------------------	-------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	4.6 cm
------------------	--------

Package 1 Width	7.0 cm
-----------------	--------

Package 1 Length	3.5 cm
------------------	--------

Package 1 Weight	20.0 g
------------------	--------

Unit Type of Package 2	S02
------------------------	-----

Number of Units in Package 2	75
------------------------------	----

Package 2 Height	15 cm
------------------	-------

Package 2 Width	30 cm
-----------------	-------

Package 2 Length	40 cm
------------------	-------

Package 2 Weight	2.815 kg
------------------	----------

Unit Type of Package 3	P12
------------------------	-----

Number of Units in Package 3	1200
------------------------------	------

Package 3 Height	100 cm
------------------	--------

Package 3 Width	125 cm
-----------------	--------

Package 3 Length	55 cm
------------------	-------

Package 3 Weight	44 kg
------------------	-------

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

Toxic heavy metal free	Yes
------------------------	-----

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration
-----------------------	--

RoHS exemption information	Yes
----------------------------	-----

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
---------------------------	---

Recommended replacement(s)