SWITCHING ADAPTER PART NUMBER CONFIGURATION

WALL MOUNT TYPE AC ADAPTER

TRXXXX - X - XX X XX

Model No.	AC Plug Type	DC Plug Type	OVP Option	DC Cable Length and Type
	A : USA 2 Pin E : Europe 2 Pin U : British 3 Pin S : Australia 2 Pin	**Straight/Inner+Outer-** (+ —●)— − 11 : 5.5 x 2.1 x 12mm 12 : 5.5 x 2.5 x 12mm 18 : 5.5 x 2.5 x 11mm 23 : 5.5 x 2.1 x 9.5mm 26 : 5.5 x 2.5 x 9.5mm 32 : 5.5 x 2.1 x 7.5mm 33 : 5.5 x 2.1 x 11.5mm 35 : 4.0 x 1.7 x 9.5mm 37 : 5.5 x 2.5 x 7.5mm 39 : 3.5 x 1.35 x 9mm 41 : 3.5 x 1.35 x 7.5mm 45 : 4.75 x 1.7 x 9.5mm 50 : 4.0 x 1.7 x 11mm **Right Angle/Inner+Outer-** (+ —●)— − 01 : 5.5 x 2.1 x 12mm 02 : 5.5 x 2.5 x 12mm 17 : 5.5 x 2.1 x 11mm 19 : 5.5 x 2.5 x 10.5mm 20 : 5.5 x 2.5 x 9mm 21 : 5.5 x 2.5 x 9.5mm 24 : 5.5 x 2.1 x 9.5mm 31 : 3.5 x 1.35 x 7.5mm 34 : 5.5 x 2.1 x 11.5mm 36 : 3.5 x 1.35 x 9mm 40 : 4.0 x 1.7 x 9.5mm 42 : 3.5 x 1.35 x 9.5mm 46 : 4.0 x 1.7 x 12mm 48 : 5 x 1.5 x 9.5mm 49 : 2.35 x 0.7 x 9.5mm **Straight/Inner-Outer+** − —●)— + 05 : 5.5 x 2.1 x 12mm 13 : 5.5 x 2.1 x 12mm 14 : 5.5 x 2.5 x 12mm 27 : 5.5 x 2.5 x 9.5mm **Right Angle / Inner-Outer+** − —●)— + 03 : 5.5 x 2.1 x 12mm 04 : 5.5 x 2.5 x 12mm 16 : 5.5 x 2.1 x 11mm 22 : 5.5 x 2.5 x 9.5mm 43 : 5.5 x 2.1 x 9.5mm 44 : 3.5 x 1.35 x 7.5mm 105 : 3.5 x 1.05 x 9.5mm 111 : 3.5 x 1.35 x 9.5mm 122 : 3.5 x 1.35 x 12mm 141 : 5.5 x 2.1 x 11mm 150 : 3.5 x 1.35 x 9mm 317 : 5.5 x 2.5 x 9mm	A: Without OVP Option E: With OVP Option	01: 720mm 02:1220mm 03:1800mm 11:720mm with Ferrite Core 12:1220mm with Ferrite Core 13:1800mm with Ferrite Core

DESK TOP TYPE AC ADAPTER

TRXXXXX - XX X XX

Model No.	DC Plug Type	OVP Option	DC Cable Length and Type
	Straight/Inner+Outer- (+ —●)— − 11 : 5.5 x 2.1 x 12mm 12 : 5.5 x 2.5 x 12mm 18 : 5.5 x 2.5 x 11mm 23 : 5.5 x 2.1 x 9.5mm 26 : 5.5 x 2.5 x 9.5mm 32 : 5.5 x 2.1 x 7.5mm 33 : 5.5 x 2.1 x 11.5mm 35 : 4.0 x 1.7 x 9.5mm 37 : 5.5 x 2.5 x 7.5mm 39 : 3.5 x 1.35 x 9mm 41 : 3.5 x 1.35 x 7.5mm 45 : 4.75 x 1.7 x 9.5mm 50 : 4.0 x 1.7 x 11mm **Right Angle/Inner+Outer-** (+ —●)— − 01 : 5.5 x 2.1 x 12mm 02 : 5.5 x 2.5 x 12mm 17 : 5.5 x 2.1 x 11mm 19 : 5.5 x 2.5 x 10.5mm 20 : 5.5 x 2.5 x 9mm 21 : 5.5 x 2.5 x 9.5mm 24 : 5.5 x 2.1 x 9.5mm 31 : 3.5 x 1.35 x 7.5mm 34 : 5.5 x 2.1 x 11.5mm 36 : 3.5 x 1.35 x 9mm 40 : 4.0 x 1.7 x 9.5mm 42 : 3.5 x 1.35 x 9.5mm 46 :4.0 x 1.7 x 12mm 48 : 5 x 1.5 x 9.5mm 49 : 2.35 x 0.7 x 9.5mm **Straight/Inner-Outer+** − —●)— + 05 : 5.5 x 2.1 x 12mm 13 : 5.5 x 2.1 x 12mm 14 : 5.5 x 2.5 x 12mm 27 : 5.5 x 2.5 x 9.5mm **Right Angle/Inner-Outer+** − —●)— + 03 : 5.5 x 2.1 x 12mm 04 : 5.5 x 2.5 x 12mm 16 : 5.5 x 2.1 x 11mm 22 : 5.5 x 2.5 x 9.5mm 43 : 5.5 x 2.1 x 9.5mm 44 : 3.5 x 1.35 x 7.5mm	A: Without OVP Option E : With OVP Option	01:720mm 02:1220mm 03:1800mm 11:720mm with Ferrite Core 12:1220mm with Ferrite Core 13:1800mm with Ferrite Core

Cincon offers a wide variety of DC plugs for every customers.
Please contact your distributor or E-Mail sales@cincon.com.tw for more information.