

TRB245

ALL-IN-ONE INDUSTRIAL M2M LTE CAT 4 GATEWAY

Industrial All-In-One M2M LTE Cat 4 Gateway equipped with multiple Inputs/Outputs, RS232, RS485 and Ethernet interfaces. All these features allow this device to be used universally in M2M applications.



LTE Cat 4 up to 150 Mbps



RS232/RS485 serial communication interfaces



Wide range of power supply voltages



Dual-SIM with auto Failover, Backup WAN and other SW features



Multiple Inputs/Outputs for remote monitoring and control



Teltonika Remote Management System compatible

PROFESSIONAL


- Ethernet port and LTE Cat 4 for high data throughput
- High processing power
- Convenient router access via Remote Management System

RELIABLE

- WAN failover using 4 separate WAN Interfaces
- Dual redundant power supplies
- Multiple connection/service watchdogs

SECURE

- Advanced WiFi encryption
- Advanced Firewall functionality
- Continuous firmware updates



Hardware

Mobile	4G/LTE (Cat 4), 3G, 2G
CPU	Qualcomm, MIPS 24Kc, 650 MHz
Memory	16 MBytes Flash, 64 MBytes RAM
Powering option	16pin terminal, 9-30 VDC
SIM	2 x Internal SIM holders (2FF)
Antenna connectors	1 x SMA for mobile, 1 x SMA for GPS
Ethernet	1 x 10/100 Ethernet port
GNSS	GPS, GLONASS, BeiDou, Galileo, QZSS
Inputs/Outputs	On 16pin socket: 3 x Digital input/Digital open collector output (configurable), 1 x Analog input
Serial	1 x RS232, 1 x RS485
Status LEDs	3 x Connection type, 3 x Signal strength, 2 x Ethernet, 1 x Power
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with DIN rail mounting option
Dimensions (W x H x D)	83 x 25 x 74 mm
Weight	165 g

Software

Operating system	RutOS (OpenWrt based Linux OS)
Mobile features	Multiple PDN, Auto APN, Band lock, SIM switch, Operator black/white list, Data/SMS limits
Network protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, DHCP, Telnet
Monitoring and Management	WEB UI, CLI, SSH, SMS, TR-069, SNMP, JSON-RPC, MQTT, RMS
Connection monitoring	Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection
Cloud solutions	RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
NTP	NTP Server, NTP Client, Sync with: External NTP server, GNSS, Mobile operator
GNSS	NMEA forwarding, AVL, Geofencing
Modbus	TCP slave, TCP master, RTU master, RTU gateway, Modbus over MQTT
Serial	Console, Over IP, Modem, NTRIP, Modbus
Administration	Multi user, Configuration profiles, Diagnostics, logs, Configuration backup