UQS-COB-12W-WW-24V		
Professional Led Strip, 12W/m		POS
		■ Features:
and the second second	and the second second	Uniform lighting
+00247 - +0024	V +BOAR OF THE	• Uniform light line and high luminous intensity
	000 000	
CHO CHO GHO		• 3 years warranty
TECHNICAL DETAILS	GND. CND CND	VEK C E 3 IP33 CRI > 90 Image: Second s
MODEL	UQS-COB-12W-WW-24V	EPREL
Supply voltage	24V ± 0.5Vdc	
Power	12W/m (60W/reel)	ENERG [*]
Current	0.33 A/m (1.65A/roll)	MW LIGHTING
Power per reel	60W	UQS-COB-12W-WW-24V
Color temperature	3000К	A
Beam angle	180°	B
Luminous flux	1060 lm/m (3700lm/roll)	
CRI	>90	
Maximum length for one sided supply	5m	
IP protection degree	IP20	
Working temperature	-20°C ÷ 50°C	
Storage temperature	-30°C ÷ 80°C	GGG
LED QTY	480 LEDs/m (1600 LEDs/reel)	6
Width PCB	10mm	kWh/1000h
Cut section	50m	
Connection wire	2 x AWG20 (0.52 mm2) stranded wire length = 360 mm: V+: red: V-:black.	
Dimensions (L x W x H)	5004 x 10 x 2.2 mm	
Packing	5m / reel (bag)	

MECHANICAL SPECIFICATION:

