

# Measured by XTAR 14500 800mAh Moonlight Output 2lm 33days Beam distance: 175m, intensity: 7500CD Low mode 20lm 13.6hrs Mid Mode 200lm 1.58hrs High mode/Strobe/SOS. 500lm 47mins









#### [ Great Compatibility ]

Powered by 1xAA Ni-MH/ 1xAA ALKA/1x14500 Li-ion batteries

### Adjustable Focus

Zoom in for an intense beam or out for wider illumination with convex lens





### [Compact Shape]

Perfect combination of trustworthiness and appearance with compact shape







[Protection]

Impact resistant 1.5M, waterproof IPX5



## [ Design ]

# Max tactical design Compact for one handed operation

Intuitive interface ensures unprecedented ease of use

### [Weight]

Only 50g weight with belt clip for EDC, Provide you assistance and convenience

Anti-rolling design for better loss prevention





#### [ Mode Memory ]

Intelligent memory function stores preferred brightness setting [CREE-XP-G3]

High brightness with maximum output 500lm



# [WK007 Specification]

ANSI	Illumination levels					
	High	Mid	Low	Moonlight	Strobe	Signal
پاند Luminance	500lm	200lm	30lm	2lm	500lm	500lm
O Runtime (XTAR 14500 800mAh)	47mins	1.58hrs	13.6hrs	33days	N/A	N/A
Beam Throw	175m					
Max Intensity	7500CD					
Adjustable Focus	12.5mm					
✓ Impact Resistant	1.5m					
<b>™</b> Waterproof	IPX5					
LED	CREE-XP-G3					
Switch	Tail tap switch					
Battery	1xAA NI-MH/1xAA ALKA/1x14500 Li-ion battery					
Body Material	Anodized aircraft 6N03 aluminum alloy; Type III hard-anodized anti-corrosion finish					
Size	28.5mm(head)x19.5 (body)x22mm (tail)x100mm(length)					
Net Weight	50g(battery excluded)					
Package Contents	Flashlight, stainless stell clip, manual, warranty card, lanyard, spare o-ring					

Notice: The above-mentioned parameters were lab tested which are approximate. Parameters may vary depending on the flashlights, chargers, batteries and environments.

### [ Packaging Contents ]

Flashlight, stainless stell clip, manual, warranty card, lanyard, spare o-ring





